

FLARE-B

29 x 23 mm lens with ~100° x 10° oval beam


TECHNICAL SPECIFICATIONS:

Dimensions	29 x 23 mm
Height	12.7 mm
Fastening	glue, screw
Colour	clear
Box size	460 x 250 x 300 mm
Box weight	8.6 kg
Quantity in Box	1792 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:


Component	Type	Material	Colour
FLARE-B	Lens	PMMA	clear





PHOTOMETRIC DATA (MEASURED):





LED XB-D
FWHM 10.0 + 108.0°
Efficiency 93 %
Peak intensity 1.520 cd/lm
Required components:





LED XP-E
FWHM 12.0 + 96.0°
Efficiency 94 %
Peak intensity cd/lm
Required components:



LED XP-G
FWHM 14.0 + 112.0°
Efficiency 95 %
Peak intensity cd/lm
Required components:




LED LUXEON Rebel
FWHM 11.0 + 93.0°
Efficiency 94 %
Peak intensity cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):





LED LUXEON Rebel ES
FWHM 12.0 + 104.0°
Efficiency 94 %
Peak intensity 1.370 cd/lm
Required components:





LED NCSxx19A
FWHM 9.0 + 88.0°
Efficiency 94 %
Peak intensity cd/lm
Required components:



LED Oslon SSL 150
FWHM 9.0 + 117.0°
Efficiency 93 %
Peak intensity 1.600 cd/lm
Required components:





LED Oslon SSL 80
FWHM 9.0 + 88.0°
Efficiency 95 %
Peak intensity cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):

SAMSUNG


LED LH351Z
FWHM 14.0 + 106.0°
Efficiency 94 %
Peak intensity 1.900 cd/lm
Required components:



LED Z5
FWHM 12.0 + 96.0°
Efficiency %
Peak intensity cd/lm
Required components:

SHARP


LED Double Dome (GM2BB)
FWHM 11.0 + 104.0°
Efficiency %
Peak intensity cd/lm
Required components:



PHOTOMETRIC DATA (SIMULATED):



LED MHB-A/B
FWHM 26.0 + 100.0°
Efficiency 94 %
Peak intensity 0.970 cd/lm
Required components:




LED XP-E2
FWHM 18.0 + 108.0°
Efficiency 94 %
Peak intensity 1.590 cd/lm
Required components:



LED XP-G2
FWHM 22.0 + 108.0°
Efficiency 94 %
Peak intensity 1.370 cd/lm
Required components:



LED Duris S8
FWHM 19.0 + 97.0°
Efficiency 94 %
Peak intensity 1.240 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ledil:

[C10946_FLARE-B](#)