

4.2mm Male Terminal / Female Housing / Crimp Female Housing

Specifications

Current Rating: 9A AC,DC

Voltage Rating: 600V AC,DC

Temperature Range: 4200H: -25°C to +85°C




4200HA: -40°C to +105°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute


Material: Nylon 66, UL94V-2







Wire Range	Insulation O.D.	Material	Finish
#18-#24	3.10mm(Max)	Brass	Tin Plated

Part No.:4200-MT-L

No. of Contacts	Dimensions	
	A	B
2x1	---	5.40
2x2	4.20	9.60
2x3	8.40	13.80
2x4	12.60	18.00
2x5	16.80	22.20
2x6	21.00	26.40
2x7	25.20	30.60
2x8	29.40	34.80
2x9	33.60	39.00
2x10	37.80	43.20
2x11	42.00	47.40
2x12	46.20	51.60





Part No.:4200H-F2XXW-L



No. of Contacts	Dimensions	
	A	B
02	4.20	9.60
03	8.40	13.80
04	12.60	18.00
05	16.80	22.20

Part No.:4200H-F1XXW-L

Dimensional Information (mm)					
Contacts	Dim. A	Dim. B	Dim. C	Dim. D	Dim. E
2x1	5.4	11.6	12.1	15.6	
2x2	4.2	9.6	15.8	16.3	19.8
2x3	8.4	13.8	20.0	20.5	24.0
2x4	12.6	18.0	24.2	24.7	28.2
2x5	16.8	22.2	28.4	28.9	32.4
2x6	21.0	26.4	32.6	33.1	36.6
2x7	25.2	30.6	36.8	37.3	40.8
2x8	29.4	34.8	41.0	41.5	45.0
2x9	33.6	39.0	45.2	45.7	49.2
2x10	37.8	43.2	49.4	49.9	53.4
2x11	42.0	47.4	53.6	54.1	57.6
2x12	46.2	51.6	57.8	58.3	61.8



Part No.:4200HA-F2XXW-L