


Type DPP Polypropylene Radial Leaded Film Capacitors

High Frequency

Film/Foil

Precise Values

Radial Leaded



Type DPP radial leaded polypropylene film/foil capacitors are non-inductively wound. Very low dissipation factor and high insulation resistance contribute to excellent performance and long-term stability characteristics. Low ESR, DF and its inherent stability make **Type DPP** an ideal choice for tight tolerance, pulse and high-frequency applications.

Specifications

Capacitance Range: 0.001 to 0.47 μ F

Voltage Range: 100 to 630 Vdc
(70 to 250 Vac, 60 Hz)

Capacitance Tolerance: $\pm 10\%$ standard,
 $\pm 5\%$ optional

Operating Temperature Range: -55°C to $+105^{\circ}\text{C}^*$

*Full rated voltage at 85°C , derated linearly to 50% rated voltage at $+105^{\circ}\text{C}$

Dielectric Strength: 200% (1 minute)


Dissipation Factor: 0.10% Max. ($+25^{\circ}\text{C}$, 1 kHz)

Insulation Resistance: 50,000 $\text{M}\Omega \cdot \mu\text{F}$,
100,000 $\text{M}\Omega$ Min.

Life Test: 1000 hr at 85°C at 125% rated voltage



Complies with the EU Directive 2002/95/EC requirement restricting the use of Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent chromium (Cr(VI)), PolyBrominated Biphenyls (PBB) and PolyBrominated Diphenyl Ethers (PBDE).



NOTE: Other capacitance values, sizes and performance specifications are available. Please contact CDE.

Ratings

Catalog						
Cap (μ F)	Part Number	T Max. Inches (mm)	H Max. Inches (mm)	L Max. Inches (mm)	S ± 0.06 (± 1.5) Inches (mm)	d ± 0.05 (1.27) Inches (mm)
100 Vdc (70 Vac 60 Hz)						
.033	DPP1S33K-F	0.315 (8.0)	0.532 (13.5)	0.768 (19.5)	0.591 (15.0)	.024 (.6)
.047	DPP1S47K-F	0.335 (8.5)	0.610 (15.5)	0.768 (19.5)	0.591 (15.0)	.024 (.6)
.068	DPP1S68K-F	0.374 (9.5)	0.650 (16.5)	0.788 (20.0)	0.591 (15.0)	.024 (.6)
.10	DPP1P1K-F	0.394 (10.4)	0.670 (17.0)	1.024 (26.0)	0.788 (20.0)	.024 (.6)
.15	DPP1P15K-F	0.433 (11.0)	0.748 (19.0)	1.024 (26.0)	0.788 (20.0)	.032 (.8)
.22	DPP1P22K-F	0.512 (13.0)	0.748 (19.0)	1.024 (26.0)	0.788 (20.0)	.032 (.8)
.33	DPP1P33K-F	0.551 (14.0)	0.827 (21.0)	1.260 (32.0)	1.083 (27.5)	.032 (.8)
.47	DPP1P47K-F	0.630 (16.0)	0.945 (24.0)	1.260 (32.0)	1.083 (27.5)	.032 (.8)
250 Vdc (140 Vac 60 Hz)						
.010	DPP2S1K-F	0.276 (7.0)	0.473 (12.0)	0.591 (15.0)	0.394 (10.0)	0.024 (.6)
.015	DPP2S15K-F	0.295 (7.5)	0.473 (12.0)	0.591 (15.0)	0.394 (10.0)	0.024 (.6)
.022	DPP2S22K-F	0.315 (8.0)	0.512 (13.0)	0.591 (15.0)	0.394 (10.0)	0.024 (.6)

Type DPP Polypropylene Radial Leaded Film Capacitors

Catalog						
Cap (μ F)	Part Number	T Max. Inches (mm)	H Max. Inches (mm)	L Max. Inches (mm)	S ± 0.06 (± 1.5) Inches (mm)	d ± 0.05 (1.27) Inches (mm)
250 Vdc (140 Vac 60 Hz)						
.033	DPP2S33K-F	0.335 (8.5)	0.551 (14.0)	0.788 (20.0)	0.591 (15.0)	0.024 (.6)
.047	DPP2S47K-F	0.354 (9.0)	0.630 (16.0)	0.788 (20.0)	0.591 (15.0)	0.024 (.6)
.068	DPP2S68K-F	0.433 (11.0)	0.630 (16.0)	0.788 (20.0)	0.591 (15.0)	0.024 (.6)
.10	DPP2P1K-F	0.394 (10.0)	0.709 (18.0)	1.024 (26.0)	0.788 (20.0)	0.032 (.8)
.15	DPP2P15K-F	0.473 (12.0)	0.866 (22.0)	1.024 (26.0)	0.788 (20.0)	0.032 (.8)
.22	DPP2P22K-F	0.551 (14.0)	0.945 (24.0)	1.024 (26.0)	0.788 (20.0)	0.032 (.8)
.33	DPP2P33K-F	0.591 (15.0)	0.985 (25.0)	1.260 (32.0)	1.083 (27.5)	0.032 (.8)
.47	DPP2P47K-F	0.680 (16.0)	1.063 (27.0)	1.260 (32.0)	1.083 (27.5)	0.032 (.8)
400 Vdc (250 Vac 60 Hz)						
.010	DPP4S1K-F	0.335 (8.5)	0.551 (14.0)	0.591 (15.0)	0.394 (10.0)	0.024 (.6)
.015	DPP4S15K-F	0.354 (9.0)	0.591 (15.0)	0.591 (15.0)	0.394 (10.0)	0.024 (.6)
.022	DPP4S22K-F	0.394 (10.0)	0.670 (17.0)	0.768 (19.5)	0.591 (15.0)	0.024 (.6)
.033	DPP4S33K-F	0.394 (10.0)	0.670 (17.0)	0.768 (19.5)	0.591 (15.0)	0.024 (.6)
.047	DPP4S47K-F	0.354 (9.0)	0.630 (16.0)	1.024 (26.0)	0.788 (20.0)	0.032 (.8)
.068	DPP4S68K-F	0.433 (11.0)	0.709 (18.0)	1.024 (26.0)	0.788 (20.0)	0.032 (.8)
.10	DPP4P1K-F	0.473 (12.0)	0.788 (20.0)	1.260 (32.0)	1.083 (27.5)	0.032 (.8)
.15	DPP4P15K-F	0.473 (12.0)	0.906 (23.0)	1.260 (32.0)	1.083 (27.5)	0.032 (.8)
630 Vdc (250 Vac 60 Hz)						
.0010	DPP6 D1K-F	0.256 (6.5)	0.492 (12.5)	0.591 (15.0)	0.394 (10.0)	.024 (.6)
.0015	DPP6 D15K-F	0.276 (7.0)	0.492 (12.5)	0.591 (15.0)	0.394 (10.0)	.024 (.6)
.0022	DPP6 D22K-F	0.276 (7.0)	0.492 (12.5)	0.591 (15.0)	0.394 (10.0)	.024 (.6)
.0033	DPP6 D33K-F	0.295 (7.5)	0.473 (12.0)	0.768 (19.5)	0.591 (15.0)	.024 (.6)
.0047	DPP6 D47K-F	0.315 (8.0)	0.492 (12.5)	0.768 (19.5)	0.591 (15.0)	.024 (.6)
.0068	DPP6 D68K-F	0.354 (9.0)	0.551 (14.0)	0.768 (19.5)	0.591 (15.0)	.024 (.6)
.010	DPP6S1K-F	0.354 (9.0)	0.551 (14.0)	1.024 (26.0)	0.788 (20.0)	.024 (.6)
.015	DPP6S15K-F	0.394 (10.0)	0.630 (16.0)	1.024 (26.0)	0.788 (20.0)	.024 (.6)
.022	DPP6S22K-F	0.433 (11.0)	0.670 (17.0)	1.024 (26.0)	0.788 (20.0)	.024 (.6)
.033	DPP6S33K-F	0.433 (11.0)	0.670 (17.0)	1.260 (32.0)	1.083 (27.5)	.032 (.8)
.047	DPP6S47K-F	0.492 (12.5)	0.748 (19.0)	1.260 (32.0)	1.083 (27.5)	.032 (.8)
.068	DPP6S68K-F	0.551 (14.0)	0.866 (22.0)	1.260 (32.0)	1.083 (27.5)	.032 (.8)
.100	DPP6P1K-F	0.512 (13.0)	0.866 (22.0)	1.260 (32.0)	1.083 (27.5)	.032 (.8)

Notice and Disclaimer: All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.