



| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A | 27,4 |
| B | 14,2 |
| C | 3,2 |
| D | 24,7 |
| E | 22,4 |
| F | 24,6 |
| G | 32,5 |
| H | 3,2 |

| NO. | BESCHREIBUNG / DESCRIPTION |
|-----|-------------------------------------|
| 1 | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 5 | KONTAKTSTIFT/ CONTACT PIN |
| 8 | DOSENGEHÄUSE / SHELL |

Note: Due to an automatic nomenclature system, numbers generated may not be sequential.
 Specification and Dimensions subject to change
 Drawings illustrate normal insulator positioning

| Material Specification: | |
|-------------------------|-----------------|
| Shell Material: | Aluminium alloy |
| Shell Plating: | Nickel plated |
| Insulator Material: | CR-Elastomere |
| Contact Material: | Copper alloy |
| Contact Plating: | Hard silver |

all dimensions are in mm
 Dimensions without tolerance indications are general tolerances in acc. with DIN7188m
 drawing for CUSTOMER



description CA02COM-E16S-1P-B
 Box mounting receptacle
 Solder Cup / Pin / Layout: 16S-1