

One-stop shopping,  
just for the sake of customers

[Search](#)

Selection For Components  
You Need





- ❖ Connectors
- ❖ RF Connectors \*Antennas
- ❖ Audio And video Accessories
- ❖ Terminal blocks
- ❖ Buzzers
- ❖ Potentiometers
- ❖ Fuses \* Fuse Holders
- ❖ Resistors
- ❖ Switches
- ❖ Wiring Accessories
- ❖ LEDs\*LED Displays\*LCD Displays And Modules
- ❖ Capacitors
- ❖ KWH Meter Accessories
- ❖ Communication Accessories
- ❖ Quartz Crystal Units \*

Ceramic Resonators




- ❖ PCB \* PCB Assembly
- ❖ Flat Cables \* Cable Assemblies
- ❖ Inductors
- ❖ Relays\*Discrete Semiconductors

Products

**KLS1-218B (2.0mm)**



P.C.B Layout



Position	1 Thru 40
Dimension	2 Thru 80
A±0.20	2.0xNo. of Positions
B±0.15	2.0xNo. of Positions-2.0

2.0mm pitch

Order Information

KLS1-218B-1-XX-S-L1\*L2\*L3

1-Single layer 2-Double layer

XX-Total pin number (No.of 1~80pin)

S-Straight R-Right T-SMT Pin

L1 Size / L2 Size / L3 Size

**Material:**

Housing: NYLON-6T , UL94V-0

Contacts: Brass

Plating: Selective gold plated: 0.8u" over 50u" nickel

**Electrical Characteristics:**

Current Rating: 1 AMP

Insulator Resistance: 5000M Ohm min. at DC 500V

Contact Resistance: 20m Ohm max. at DC 100mA

Operating Temperature: -45°C~+105°C

 **Back**

Inquiry E-mail: [sales@cnkls.com](mailto:sales@cnkls.com)

General manager Complaints E-mail: [manager@cnkls.com](mailto:manager@cnkls.com)

All your enquiry will be send to [China Cheap Electronics](#) professional sales manager immediately and reply you within 3 working days!