

Data Sheet

LL01CR-ABHxxL02


XLamp CXA1507


■ Features & Typical Applications

- High efficiency
- Available with 2 beam angles
- Optimized for uniform effect
- Lens without Housing
- Commercial Lighting
- Architectural Lighting
- Highbay

■ Table of Contents


General Information & Product Nomenclature.....	P.2
Optical Specifications	P.3
Mechanical Specifications	P.4
Package Specifications	P.5

LL01CR-ABHxxL02

General Information

- Lens Material Optical Grade PC
- Operating Temperature range -40°C~+110°C(upper limit +120°C)
- Storage Temperature range -40°C~+110°C(upper limit +120°C)
 - * Average transmittance in visible spectrum 400nm~700nm>90%
- Usage and Maintenance:
 1. If necessary, clean lenses with mild soap, water and soft cloth.
 2. Never use any commercial cleaning solvents on lenses, like alcohol.
 3. Please handle or install lenses with wearing gloves, skin oils may damage lens or its optical characteristic.

Product Nomenclature









LL01CR-ABHxxL02

Optical Specifications



Xlamp CXA1507

Note: (1) All the results of analysis are based on 0 degrees of elevation.
 (2) Tolerance: $\pm 10\%$.
 (3) Led Luminous Flux(lm): 550($\pm 5\%$).

Part Number	FWHM	Field Angle*	cd / lm	IES File
LL01CR-ABH40L02	31°	66°	1.7	Download
				
Beam Pattern	Light Distribution Curve	Illuminance Distribution		
Part Number	FWHM	Field Angle*	cd / lm	IES File
LL01CR-ABH60L02	59°	99°	0.8	Download
				
Beam Pattern	Light Distribution Curve	Illuminance Distribution		

*The Field Angle is the angle between the two directions opposed to each other over the beam axis for which the luminous intensity is 10% that of the maximum luminous intensity.
 *This testing result is obtained through testing the popular rank LED samples which provided by the original manufacturer. Hence, the testing results would be varied as the users choose same LED model but different rank.

LL01CR-ABHxxL02

Mechanical Specification

1. Fixing method

☒ Glue

☐ Screw


☐ Tape

☐ Fixing-ring



☒ Frame

Note: (1) All dimensions are in mm.
 (2) All measurements are ± 0.15 mm unless otherwise indicated.

2. Lens dimensions




3. Lens + Leds + MCPCB assembly instruction



4. Lens assembly dimensions


5. View assembly lens with MCPCB:





LL01CR-ABHxxL02

Package Specifications

Item	Quantity	Total	Size(L*W*H)	G.W
Plastic box	25 pcs/plastic box	25 pcs	32.8*29.8*1.6 cm	8.5g
Outer box	13 plastic box/Outer box	325 pcs	35*31*21 cm	



25 pcs/plastic box



325 pcs/outer box



Note: