

LKD	3	4	V	6	2	1	K	A	-	D	1	
<b>Marking</b>	<b>Dimension ±1.0mm</b>		<b>Disc Type</b>	<b>Varistor Voltage</b>			<b>Tolerance</b>	<b>Electrode material</b>	<b>Free code</b>		<b>Lead type</b>	
LKD	19	19.5×19.5mm	A: Disc Type	The first two digits are significant figures and the third one denotes the number of zeros			K ±10%	Silver Electrode	-	ND	A 1	ABB
Long Ke	22	22.2×25.2mm	D: Round finished product	following decimal point is expressed by R.			J ±5%	Aluminium or Aluminium compound Electrode	1	Class 1	C 1	C型
Defense	34	33.5×33.5mm	S: Square finished product	Examples:					2	Class 1+2	C 2	C型双片
FSV	41	41.0×29.0mm	R Double disc	680	$68 \times 10^0 = 68V$				3	3 pcs	C 3	
Module Thermal protect Type	43	33.5×43.5mm	H: High energy surge	621	$62 \times 10^1 = 620V$				4	脚长4	D 1	中盾
TMOV	49	33.5×48.5mm	M (E/N) Thermal protect varistor	112	$11 \times 10^2 = 1100V$				5	脚长5	D 2	深盾
	<b>Diameter ±1.0mm</b>		J screwing tight						6	60KA	D 3	德国型
	14	Φ15.0 mm	X double disc screwing tight						7	70KA	D 4	高压深盾型
	20	Φ19.5 mm	V Box screwing						8		D 5	L盾型
	25	Φ25.0 mm	P Plank screwing						9		D 6	大L盾型
	32	Φ32.0 mm	W Box double disc screwing						L	1.0mm/12.5mm 脚距	D 7	
	37	Φ37.0 mm	Q Plank double screwing						P	粉醛	D 8	
	42	Φ41.3 mm							T	TMOV 专用	F 1	
	53	Φ53.0 mm							A-Z		G 1	Citel
	99	Φ99.0 mm									O 1	OBO
											O 2	LOBO
											O 3	
											P 1	菲尼
											T 1	CPT
											K 1	外弯
											K 2	青蛙
											K 3	
											K 4	
											K 5	
											K 6	内弯
											K 7	
											K 8	高低脚
											K 9	安全脚
											K 0	

  

**LKD** → Brand Mark

**34S621KA-@@** → Part No.

**I31** → Date Code Approve