

SPECIFICATION SHEET FOR HIGH SENSITIVE NO SENSOR TYPE NO/C-1

PERFORMANCE CHARACTERISTICS

Nominal Range	0 – 1 ppm
Maximum Overload	5 ppm
Expected Operation Life	2 years in air
Output Signal	5'000 ± 2'000 nA/ppm
Resolution	0.05 ppm
Temperature Range	- 20 °C to 50 °C
Pressure Range	Atmospheric ± 10%
Pressure Coefficient	No data
T ₉₀ Response Time	< 40 sec
Relative Humidity Range	15 % to 90 % R.H. non-condensing ^(*)
Typical Baseline Range (pure air, 20°C)	+ 0.1 to + 0.5 ppm
Maximum Zero Shift (+20°C to +40°C)	1.5 ppm
Long Term Output Drift	ND
Recommended Load Resistor	10 Ohm
Bias Voltage	+ 300 mV
Repeatability	< 2 % of signal
Output Linearity	Linear

(*) The sensor has no protection against condensation

CROSS-SENSITIVITY DATA

Interfering Gas	Concentration	Reading
CO	300 ppm	0 ppm
H ₂ S	15 ppm	< 5 ppm
NO ₂	20 ppm	< 5 ppm
H ₂	300 ppm	0 ppm
SO ₂	5 ppm	0 ppm

Performance data conditions:
20 °C, 50% RH and 1013 mbar

APPLICATIONS


Air Quality Monitoring
Environmental Control

PHYSICAL CHARACTERISTICS


Weight	~ 13 g
Position Sensitivity	None
Storage Life	Six months in container
Recommended Storage Temperature	5 °C – 20 °C
Warranty Period	12 months from date of dispatch

Compact-Size Outline Dimensions

BOTTOM VIEW



SIDE VIEW



ATTENTION

Do not press anything against the grid on the top.

The data contained in this document is for guidance only. Membrapor AG accepts no liability for any consequential losses, injury or damage resulting from the use of this document or the information contained within it. The data is given for guidance only. Customers should test under their own conditions, to ensure that the sensors are suitable for their own requirements.

REV.: 08/2013

Page 1 of 1

Phone: +41 43 311 72 00
Fax : +41 43 311 72 01
Email: info@membrapor.ch
www.membrapor.ch

MEMBRAPOR AG
Birkenweg 2
CH-8304 Wallisellen
Switzerland