



- Recyclable packing available
- 16 mm profile
- IP 40 & IP 67
- Plug-in mounting for 1C/O
- Wide range of accessories for 1C/O

Contacts

Contact number & arrangement		1C/O, 1NO, 1NC
Contact material		AgCdO , AgSnO ₂
Max. switching voltage	AC/DC	400 V / 250 V
Min. switching voltage		10 V AgCdO, 10 V AgSnO ₂
Rated load	AC1	8 A / 250 V AC
	DC1	8 A / 24 V DC
Min. switching current		5 mA AgCdO, 10 mA AgSnO ₂
Rated current		8 A
Max. breaking capacity	AC1	2 000 VA
Min. breaking capacity		0,5 W AgCdO, 1 W AgSnO ₂
Resistance		≤ 100 mΩ
Max. operating frequency	AC1	• at rated load
		• no load
		600 cycles/hour
		72 000 cycles/hour

Coil

Rated voltage	DC	5...48 V
Must release voltage		≥ 0,1 U _n
Operating range of supply voltage		see Table 1
Rated power consumption	DC	0,3 W

Insulation

Insulation category		C250
Insulation rated voltage		400 V AC
Dielectric strength:	• coil-contact	4 000 V AC
	• contact-contact	1 000 V AC
Contact-coil distance	• clearance	≥ 8 mm
	• creepage	≥ 8 mm
		≥ 8 mm

General data


Operating time (typical value)		10 ms
Release time (typical value)		5 ms
Electrical life	• resistive	> 10 ⁵ 8 A, 250 V AC
	• cos φ	see Fig. 2, 3
Mechanical life (cycles)		> 2 x 10 ⁷
Dimensions (L x W x H)		28(30-1C/O) x 10 x 16,2 mm
Weight		11 g
Ambient temperature	• operating	-40...+85 °C
	• storing	-40...+80 °C
Cover protection category		IP 40 or IP 67
Shock resistance		20 g
Vibration resistance		10 g 10...150 Hz
Solder bath temperature		max. 270 °C
Soldering time		max. 5 s

Coil data


Table 1

Coil code	Rated voltage V DC	Coil resistance (±10%) at 20 °C Ω	Coil operating range at 20 °C V DC	
			min.	max.
1005	5	110	3,5	12,0
1006	6	160	4,2	14,5
1009	9	360	6,3	22,0
1012	12	660	8,4	29,5
1018	18	1 500	12,6	44,0
1024	24	2 200	16,8	54,0
1048	48	8 000	33,6	102,0

Dimensions




Connections diagram (pin side view)




Max. AC and DC resistive load breaking capacity

Fig. 1




Electrical life at AC resistive load (NO version)

Fig.2



Electrical life reduction factor at AC inductive load

Fig.3



Mounting

See Tables, pages 132, 133.

Ordering codes

