



|                     | PLA132 | Units |
|---------------------|--------|-------|
| Load Voltage        | 50     | V     |
| Load Current        | 600    | mA    |
| Max R <sub>ON</sub> | 1      | Ω     |

### Features

- Small 6 Pin DIP Package
- Low Drive Power Requirements (TTL/CMOS Compatible)
- No Moving Parts
- High Reliability
- Arc-Free With No Snubbing Circuits
- 3750V<sub>RMS</sub> Input/Output Isolation
- FCC Compatible
- VDE Compatible
- No EMI/RFI Generation
- Machine Insertable, Wave Solderable
- Surface Mount and Tape & Reel Versions Available

### Applications

- Instrumentation
  - Multiplexers
  - Data Acquisition
  - Electronic Switching
  - I/O Subsystems
  - Meters (Watt-Hour, Water, Gas)
- Medical Equipment—Patient/Equipment Isolation
- Security
- Aerospace
- Industrial Controls
- Automotive

### Description

PLA132 is a 50V, 600mA, 1Ω 1-Form-A relay. This performance leader features very high load current handling capabilities.

### Approvals

- UL Recognized: File Number E76270
- CSA Certified: File Number LR 43639-10
- BSI Certified to:
  - BS EN 60950:1992 (BS7002:1992)  
Certificate #: 7344
  - BS EN 41003:1993  
Certificate #: 7344


### Ordering Information

| Part #    | Description                      |
|-----------|----------------------------------|
| PLA132    | 6 Pin DIP (50/Tube)              |
| PLA132S   | 6 Pin Surface Mount (50/Tube)    |
| PLA132STR | 6 Pin Surface Mount (1,000/Reel) |

### Pin Configuration


#### PLA132 Pinout

AC/DC Configuration




#### PLA132 Pinout

DC Only Configuration



### Switching Characteristics of Normally Open (Form A) Devices



**Absolute Maximum Ratings (@ 25° C)**

| Parameter                                  | Min  | Typ | Max              | Units            |
|--|------|-----|------------------|------------------|
| Input Power Dissipation                    | -    | -   | 150 <sup>1</sup> | mW               |
| Input Control Current                      | -    | -   | 50               | mA               |
| Peak (10ms)                                | -    | -   | 1                | A                |
| Reverse Input Voltage                      | -    | -   | 5                | V                |
| Total Power Dissipation                    | -    | -   | 800 <sup>2</sup> | mW               |
| Capacitance<br>Input to Output             | -    | 3   | -                | pF               |
| Isolation Voltage<br>Input to Output       | 3750 | -   | -                | V <sub>RMS</sub> |
| Operational Temperature                    | -40  | -   | +85              | °C               |
| Storage Temperature                        | -40  | -   | +125             | °C               |
| Soldering Temperature<br>DIP Package       | -    | -   | +260             | °C               |
| Surface Mount Package<br>(10 Seconds Max.) | -    | -   | +220             | °C               |

<sup>1</sup> Derate Linearly 1.33 mw/°C

<sup>2</sup> Derate Linearly 6.67 mw/°C


*Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this data sheet is not implied. Exposure of the device to the absolute maximum ratings for an extended period may degrade the device and effect its reliability.*

**Electrical Characteristics**


| Parameter  | Conditions                               | Symbol            | Min  | Typ | Max | Units            |
|--|--|-------------------|------|-----|-----|------------------|
| <b>Output Characteristics @ 25°C</b>             |  |                   |      |     |     |                  |
| Load Voltage (Peak)                              | -  | V <sub>L</sub>    | -    | -   | 50  | V                |
| Load Current (Continuous)<br>AC/DC Configuration | -  | I <sub>L</sub>    | -    | -   | 600 | mA               |
| DC Configuration                                 | -  | I <sub>L</sub>    | -    | -   | 1.2 | A                |
| Peak Load Current                                | 10ms                                     | I <sub>LPK</sub>  | -    | -   | 2.0 | A                |
| On-Resistance<br>AC/DC Configuration             | I <sub>L</sub> =600mA                    | R <sub>ON</sub>   | -    | -   | 1.0 | Ω                |
| DC Configuration                                 | I <sub>L</sub> =1.0A                     | R <sub>ON</sub>   | -    | -   | 0.3 | Ω                |
| Off-State Leakage Current                        | V <sub>L</sub> =50V                      | I <sub>LEAK</sub> | -    | -   | 1   | μA               |
| Switching Speeds                                 |  |                   |      |     |     |                  |
| Turn-On  | I <sub>F</sub> =5mA, V <sub>L</sub> =10V | T <sub>ON</sub>   | -    | -   | 5   | ms               |
| Turn-Off   | I <sub>F</sub> =5mA, V <sub>L</sub> =10V | T <sub>OFF</sub>  | -    | -   | 2   | ms               |
| Output Capacitance                               | 50V; f=1MHz                              | -                 | -    | 100 | -   | pF               |
| <b>Input Characteristics @ 25°C</b>              |  |                   |      |     |     |                  |
| Input Control Current                            | I <sub>L</sub> =600mA                    | I <sub>F</sub>    | 5    | -   | 50  | mA               |
| Input Dropout Current                            | -  | I <sub>F</sub>    | 0.4  | 0.7 | -   | mA               |
| Input Voltage Drop                               | I <sub>F</sub> =10mA                     | V <sub>F</sub>    | 0.9  | 1.2 | 1.4 | V                |
| Reverse Input Voltage                            | -  | V <sub>R</sub>    | -    | -   | 5   | V                |
| Reverse Input Current                            | V <sub>R</sub> =5V                       | I <sub>R</sub>    | -    | -   | 10  | μA               |
| <b>Common Characteristics @ 25°C</b>             |  |                   |      |     |     |                  |
| Input to Output Capacitance                      | -  | C <sub>I/O</sub>  | -    | 3   | -   | pF               |
| Input to Output Isolation                        | -  | V <sub>I/O</sub>  | 3750 | -   | -   | V <sub>RMS</sub> |

PERFORMANCE DATA\*


**PLA132**  
Typical LED Forward Voltage Drop  
(N=50 Ambient Temperature = 25°C)  
I<sub>F</sub> = 5mADC




**PLA132**  
Typical On-Resistance Distribution  
(N=50 Ambient Temperature = 25°C)  
(Load Current = 600mADC)




**PLA132**  
Typical Blocking Voltage Distribution  
(N=50 Ambient Temperature = 25°C)




**PLA132**  
Typical I<sub>F</sub> for Switch Operation  
Ambient Temperature = 25°C  
Load Current = 600mA




**PLA132**  
Typical I<sub>F</sub> for Switch Dropout  
(N=50 Ambient Temperature = 25°C)  
(Load Current = 120mADC)




**PLA132**  
Typical Turn-On Time  
(N=50 Ambient Temperature = 25°C)  
Load Current = 600mA I<sub>F</sub> = 5mA




**PLA132**  
Typical Turn-Off Time  
(N=50 Ambient Temperature = 25°C)  
Load Current = 600mA I<sub>F</sub> = 5mA




**PLA132**  
Maximum Load Current vs. Temperature




**PLA132**  
Leakage vs. Temperature  
(Measured Across Pins 6 & 4)




**PLA132**  
Typical Blocking Voltage vs. Temperature



**PLA132**  
Typical Turn-On vs. Temperature  
Load Current = 600mA











**PLA132**  
Typical Turn-Off vs. Temperature  
Load Current = 600mA



\*The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.


PERFORMANCE DATA\*




\*The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.

MECHANICAL DIMENSIONS


6 Pin Power DIP Through Hole (Standard)




PC Board Pattern (Top View)




6 Pin Power DIP Surface Mount ("S" Suffix)



PC Board Pattern (Top View)



Tape and Reel Packaging for 6 Pin Power DIP Surface Mount Package



Dimensions  
mm  
(Inches)



# CLARE

---

**For additional information please visit our website at: [www.clare.com](http://www.clare.com)**

*Clare, Inc. makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Neither circuit patent licenses nor indemnity are expressed or implied. Except as set forth in Clare's Standard Terms and Conditions of Sale, Clare, Inc. assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.*

*The products described in this document are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or where malfunction of Clare's product may result in direct physical harm, injury, or death to a person or severe property or environmental damage. Clare, Inc. reserves the right to discontinue or make changes to its products at any time without notice.*

Specification: DS-PLA132-R1.0  
©Copyright 2002, Clare, Inc.  
OptoMOS® is a registered trademark of Clare, Inc.  
All rights reserved. Printed in USA.  
9/23/02