


Applications

- Heating and air conditioning systems
- Industrial electronics
- Automotive electronics

Features

- Uni curve sensor
- Fast response
- High temperature accuracy between 0 °C and 70 °C
- Excellent long-term stability
- Epoxy resin encapsulation
- PTFE-insulated leads of silver-plated nickel wire, AWG 30



TNT0393-9

Delivery mode

Bulk

 Dimensions in mm
 Approx. weight 60 mg

Climatic category (IEC 60068-1)		55/155/56	
Max. power at 25 °C	P_{25}	60	mW
Temperature tolerance (0 ... 70 °C)	ΔT	$\pm 0,2, \pm 0,5$	K
Rated temperature	T_N	25	°C
Dissipation factor (in air)	δ_{th}	approx. 1,5	mW/K
Thermal cooling time constant (in air)	τ_c	approx. 15	s
Heat capacity	C_{th}	approx. 22,5	mJ/K

R_{25}	No. of R/T characteristic	$B_{25/100}$	Ordering code
Ω		K	
3 k	8016	3988	B57863S0302+040
5 k	8016	3988	B57863S0502+040
10 k	8016	3988	B57863S0103+040
30 k	8018	3964	B57863S0303+040

 +: F for $\Delta T = 0,2$ K

 G for $\Delta T = 0,5$ K

For calculation of the R/T characteristics refer to our special tool "NTC R/T calculation". You may download this tool either from Internet (<http://www.epcos.com>) → Design Tools → NTC Thermistors → NTC R/T Calculation) or from the CD-ROM "Data Book Library" (Please order via Internet: Publications → General Publications).

Reliability data

Test	Standard	Test conditions	$\Delta R_{25}/R_{25}$ (typical)	Remarks
Storage in dry heat	IEC 60068-2-2	Storage at upper category temperature T: 155 °C t: 1000 h	< 1 % < 2 % ¹⁾	No visible damage
Storage in damp heat, steady state	IEC 60068-2-3	Temperature of air: 40 °C Relative humidity of air: 93 % Duration: 56 days	< 1 %	No visible damage
Rapid temperature cycling	IEC 60068-2-14	Lower test temperature: – 55 °C Upper test temperature: 155 °C Number of cycles: 100	< 1 %	No visible damage
Long-term stability (empirical value)		Temperature: 70 °C t: 10 000 h	< 2 %	No visible damage

1) For B57863S0302+040

Herausgegeben von EPCOS AG

Unternehmenskommunikation, Postfach 80 17 09, 81617 München, DEUTSCHLAND

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Vervielfältigung, Veröffentlichung, Verbreitung und Verwertung dieser Broschüre und ihres Inhalts ohne ausdrückliche Genehmigung der EPCOS AG nicht gestattet.

Bestellungen unterliegen den vom ZVEI empfohlenen Allgemeinen Lieferbedingungen für Erzeugnisse und Leistungen der Elektroindustrie, soweit nichts anderes vereinbart wird.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen Vertrieb der EPCOS AG oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse Gefahrstoffe enthalten. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft einzuholen.

Published by EPCOS AG

Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.