



1) Einlotstifte passend für Lochungen
 $\phi 1 \pm 0,1$ nach IEC 60326-3
Solder pins for PCB connections
 $\phi 1 \pm 0,1$ as per IEC 60326-3
 A souder pour des trous de $\phi 1 \pm 0,1$
 selon IEC 60326-3

| | | | | | | | | | |
|--------------------------------------|---|-----------------------|-------|---|-------------------|-------------------------------|----|--|-----------------------|
| A | 09195107322 | 3 | 4,5 | All Dimensions in mm Original Size DIN A 4 | Techn. Character. | | | Nicht tolerierte Masse! Free size tolerances | |
| | 09195106322 | 2 | 4,5 | | | | | | |
| | 09195105322 | 0,76 μm Au | 4,5 | | | | | | |
| | 09195107324 | 3 | 2,9 | | | | | | |
| | 09195106324 | 2 | 2,9 | | | | | | |
| | 09195105324 | 0,76 μm Au | 2,9 | | 36236 | 20/MAY/11 | BH | | |
| Bestell-Nr. Part-No. Reference | Anforderungsstufe performance level Niveau de qualite | a | 29778 | 25-APR-02 | CV | HARTING EURL F-95972 Paris | | TB 0919510x32x Sub. | Blatt/ page 1 2 |
| | | | 29749 | 12-FEB-02 | JB | | | | |

Dat. Name
 Detail. 12-FEB-02 JB
 Insp. 20/MAY/11 JMDV
 Stand. 1,5:1

SEK 19 Male connector
 10 poles low profile
 high T° with straight pins