



SPECIFICATIONS:

- .Insulator Material: PBT & G/F Reinforced,UL 94-V0
- .Contact Material: Phosphor bronze
- .Strain Relief Material: PBT & G/F Reinforced, UL 94-V0
- .Current rating : 1A : AWG28/1, 2A : AWG26
- .Insulation resistance : ≥1000 MΩ
- .Dielectric withstanding volatge : 500V,at sea level
- .Operating temperature : -25°C ~+85°C (limited by cable)
- .Contact resistance : ≤25mΩ
- .Wire size : AWG26 & AWG28 stranded, 1.27mm conductor center flat cable

73.95 (2.911)	70.90 (2.791)	68.50 (2.697)	73.75 (2.904)	51.84 (2.041)	74.85 (2.947)	82.80 (3.260)	5F40500P
58.85 (2.317)	53.75 (2.116)	51.50 (2.027)	58.65 (2.309)	36.72 (1.446)	59.74 (2.352)	67.80 (2.669)	5F40360P
45.88 (1.806)	37.50 (1.476)	35.50 (1.398)	45.68 (1.798)	23.76 (.935)	46.78 (1.842)	54.70 (2.154)	5F40240P
G ±0.25(.010)	F ±0.25(.010)	E ±0.25(.010)	D ±0.20(.008)	C ±0.13(.005)	B ±0.13(.005)	A ±0.25(.010)	PART NO.

RoHS Compliant **HSM 玄茂科技股份有限公司**
HSUAN MAO TECHNOLOGY CO., LTD.

APPD. 核准	SCALE 比例	TOLERANCE 容許公差	PART NAME 品名
DWG. 製圖	UNIT 單位	SIZE 紙張尺寸	CENTRONIC IDC TYPE 24F ALL PLASTIC WITH S/R BLUE COLOR ROHS
DATE 制表日	PAGE 張數	REV. 版次	PART NO. 料號
2012/12/3	1 OF 1	A	C0714-XXFAXSX0R