


Quick Disconnect - Female

Brass
Tin Plated
P.V.C. Insulation



Part No	L	B	T	H	Ø D	Ø d	Wire Size AWG(mm ²)	Current Rating	Insulation Color	Qty/Box	Weight/Box
KTL-016-01	19.0	3.2	0.5	10.0	4.0	1.7	22~16 (0.25~1.65)	10 A	Red	4000	1.6 kg
KTL-016-02	19.0	3.2	0.8							3000	1.3 kg
KTL-016-03	19.0	5.0	0.5							4000	1.2 kg
KTL-016-04	19.0	5.0	0.8							3500	1.9 kg
KTL-016-05	21.0	6.6	0.8							3000	2.4 kg
KTL-016-06	19.0	3.2	0.5	10.0	4.3	2.3	16~14 (1.04~2.63)	15 A	Blue	3000	1.4 kg
KTL-016-07	19.0	3.2	0.8							3500	1.7 kg
KTL-016-08	19.0	5.0	0.5							3000	2.0 kg
KTL-016-09	19.0	5.0	0.8							3000	1.9 kg
KTL-016-10	21.0	6.6	0.8							2500	2.2 kg
KTL-016-11	22.5	3.0	0.5	13.7	5.4	3.5	12~10 (2.63~6.64)	24 A	Yellow	2000	1.5 kg
KTL-016-12	22.5	3.0	0.8							2000	1.5 kg
KTL-016-13	23.0	5.0	0.5							2000	1.7 kg
KTL-016-14	23.0	5.0	0.8							2000	1.7 kg
KTL-016-15	25.0	6.6	0.8							1800	2.2 kg

Unit = mm