## **SNAP-IN PC CLIPS**





No Ears

- Available for "A" · "AAA" · "AAAA" · "AAAA" · "N" size batteries
  Mounts securely to the PC board with advanced "Snap-In" design for thru hole mounting
- "Snap-In" clip holds firmly for wave soldering
- Reliable spring tension assures low contact resistance
- Low profile, economical design
- Retains battery securely to withstand shock and vibration




For "AAAA"



**MATERIAL:** Spring Steel Tin Nickel Plate


For "A" · "AA" · "AAA" · "N"



.062	L H	
DIA.		Mounting Detail
	M // /	067 [1.70] DIA.
.062	.228 [5.8]	0 0
- B → [1.57]	.375 [9.5]	300 [7.6]

AT. 10.	A	В	C	Н	L	MATERIAL THICKNESS	BATTERY Diameter	BATTERY SIZE
52	.250 (6.4)		.032 (0.8)	.500 (12.7)	.280 (7.1)	.010 (.25)	No Ears	
92	.312 (7.9)	.375 (9.5)	.056 (1.4)	.593 (15.1)	.359 (9.1)	.012 (.30)	531665 (13.5-16.9)	"A" • "AA"
15	.312 (7.9)	.375 (9.5)	.050 (1.3)	.593 (15.1)	.359 (9.1)	.015 (.39)	331003 (13.3-10.8)	
32	.250 (6.4)	.300 (7.6)	.040 (1.0)	.500 (12.7)	.280 (7.1)	.010 (.25)	.375460 (9.5-11.7)	"AAA" • "N"
51	See drawing for Cat. No. 51					.010 (.25)	.300350 (7.6-8.9)	"AAAA"

Refer to page 25 for Battery Contact Layout & Mounting Details



.226 [5.7] —

MATERIAL: .010 (.25) thick Spring Steel, Tin Nickel Plate

**Mounting Detail** .055 [1.40] DIA. 

**CAT. NO. 51**