


N-CHANNEL ENHANCEMENT-MODE POWER MOSFET



Low gate-charge
Simple drive requirement
Fast switching



BV_{DS} 30V
 $R_{DS(ON)}$ 9m Ω
 I_D 60A

Description

The SSM70T03H is in a TO-252 package, which is widely used for commercial and industrial surface-mount applications, and is well suited for low voltage applications such as DC/DC converters. The through-hole version, the SSM70T03J in TO-251, is available for low-footprint vertical mounting. These devices are manufactured with an advanced process, providing improved on-resistance and switching performance. The devices have a maximum junction temperature rating of 175°C for improved thermal margin and reliability.



Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-Source Voltage	± 20	V
$I_D @ T_A = 25^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ 10\text{V}$	60	A
$I_D @ T_A = 100^\circ\text{C}$	Continuous Drain Current, $V_{GS} @ 10\text{V}$	43	A
I_{DM}	Pulsed Drain Current ¹	195	A
$P_D @ T_A = 25^\circ\text{C}$	Total Power Dissipation	53	W
	Linear Derating Factor	0.36	W/ $^\circ\text{C}$
E_{AS}	Single Pulse Avalanche Energy ³	29	mJ
T_{STG}	Storage Temperature Range	-55 to 175	$^\circ\text{C}$
T_J	Operating Junction Temperature Range	-55 to 175	$^\circ\text{C}$

Thermal Data

Symbol	Parameter	Value	Units
R_{thj-c}	Thermal Resistance Junction-case Max.	2.8	$^\circ\text{C/W}$
R_{thj-a}	Thermal Resistance Junction-ambient Max.	110	$^\circ\text{C/W}$

Electrical Characteristics@T_j=25°C(unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
BV_{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250uA	30	-	-	V
ΔBV_{DSS}/ΔT_j	Breakdown Voltage Temperature Coefficient	Reference to 25°C, I _D =1mA	-	0.032	-	V/°C
R_{DS(ON)}	Static Drain-Source On-Resistance	V _{GS} =10V, I _D =33A	-	-	9	mΩ
		V _{GS} =4.5V, I _D =20A	-	-	18	mΩ
V_{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250uA	1	-	3	V
g_{fs}		V _{DS} =10V, I _D =33A	-	35	-	S
I_{DSS}	Drain-Source Leakage Current (T _j =25°C)	V _{DS} =30V, V _{GS} =0V	-	-	1	uA
	Drain-Source Leakage Current (T _j =175°C)	V _{DS} =24V, V _{GS} =0V	-	-	250	uA
I_{GSS}	Gate-Source Leakage	V _{GS} = ±20V	-	-	±100	nA
Q_g	Total Gate Charge ²	I _D =33A	-	16.5	-	nC
Q_{gs}	Gate-Source Charge	V _{DS} =20V	-	5	-	nC
Q_{gd}	Gate-Drain ("Miller") Charge	V _{GS} =4.5V	-	10.3	-	nC
t_{d(on)}	Turn-on Delay Time ²	V _{DS} =15V	-	8.2	-	ns
t_r	Rise Time	I _D =33A	-	105	-	ns
t_{d(off)}	Turn-off Delay Time	R _G =3.3Ω, V _{GS} =10V	-	21.4	-	ns
t_f	Fall Time	R _D =0.45Ω	-	8.5	-	ns
C_{iss}	Input Capacitance	V _{GS} =0V	-	1485	-	pF
C_{oss}	Output Capacitance	V _{DS} =25V	-	245	-	pF
C_{rss}	Reverse Transfer Capacitance	f=1.0MHz	-	170	-	pF

Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_{SD}	Forward On Voltage ²	I _S =60A, V _{GS} =0V	-	-	1.3	V
t_{rr}	Reverse Recovery Time ²	I _S =30A, V _{GS} =0V,	-	29	-	ns
Q_{rr}	Reverse Recovery Charge	dI/dt=100A/μs	-	12	-	nC

Notes:

- 1.Pulse width limited by safe operating area.
- 2.Pulse width ≤300us , duty cycle ≤2%.
- 3.V_{DD}=25V , L=100uH , R_G=25Ω , I_{AS}=24A.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. On-Resistance vs. Gate Voltage




Fig 4. Normalized On-Resistance vs. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage vs. Junction Temperature




Fig 7. Gate Charge Characteristics




Fig 8. Typical Capacitance Characteristics




Fig 9. Maximum Safe Operating Area




Fig 10. Effective Transient Thermal Impedance




Fig 11. Switching Time Waveform




Fig 12. Gate Charge Waveform

Information furnished by Silicon Standard Corporation is believed to be accurate and reliable. However, Silicon Standard Corporation makes no guarantee or warranty, express or implied, as to the reliability, accuracy, timeliness or completeness of such information and assumes no responsibility for its use, or for infringement of any patent or other intellectual property rights of third parties that may result from its use. Silicon Standard reserves the right to make changes as it deems necessary to any products described herein for any reason, including without limitation enhancement in reliability, functionality or design. No license is granted, whether expressly or by implication, in relation to the use of any products described herein or to the use of any information provided herein, under any patent or other intellectual property rights of Silicon Standard Corporation or any third parties.