


2.50mm (.098") Pitch KK[®] Crimp Terminal Housing

5051-N
Polarized



Features and Benefits

- Sizes 2 to 15 circuits
- Molded friction lock
- Optional locking ramp version
- Stackable end-to-end

Reference Information

Packaging: Bulk
 UL File No.: E29179
 CSA File No.: LR19980
 Mates With: KK 2.50mm (.098") headers or 0.64mm (.025") staked pins, 5045-NA and 5046-NA
 Use With: 2759 and 5159 terminals
 Designed In: Millimeters

Electrical

Voltage: 250V
 Current: 3.0A
 Contact Resistance: 20 milliohms max.
 Dielectric Withstanding Voltage: 1000V AC/1 min.
 Insulation Resistance: 1000 Megohms min.

Physical


Housing: 6/6 nylon, UL 94V-0
 Operating Temperature: -40 to +105°C

Circuits	Order No.
2	22-01-1022
3	22-01-1032
4	22-01-1042
5	22-01-1052
6	22-01-1062
7	22-01-1072
8	22-01-1082

Circuits	Order No.
9	22-01-1092
10	22-01-1102
11	22-01-1112
12	22-01-1122
13	22-01-1132
14	22-01-1142
15	22-01-1152

2.50mm (.098") Pitch KK[®] Crimp Terminal Housing

5051-NM
Polarized



Features and Benefits

- Sizes 2 to 20 circuits
- Molded friction lock
- Optional locking ramp version
- Stackable end-to-end

Reference Information

Product Specification: PS-99020-0088
 Packaging: Bulk
 UL File No.: E29179
 CSA File No.: LR19980
 Mates With: KK 2.50mm (.098") headers or 0.64mm (.025") staked pins, 5045-NA and 5046-NA
 Use With: 2759 and 5159 terminals and 4809
 Designed In: Millimeters

Electrical

Voltage: 250V
 Current: 3.0A
 Contact Resistance: 20 milliohms max.
 Dielectric Withstanding Voltage: 1000V AC/1 min.
 Insulation Resistance: 1000 Megohms min.

Physical

Housing: 6/6 nylon, UL 94V-0
 Operating Temperature: -40 to +105°C

Circuits	Order No.
2	22-01-1023
3	22-01-1033
4	22-01-1043
5	22-01-1053
6	22-01-1063
7	22-01-1073
8	22-01-1083

Circuits	Order No.
9	22-01-1093
10	22-01-1103
11	22-01-1113
12	22-01-1123
13	22-01-1133
14	22-01-1143
15	22-01-1153

Circuits	Order No.
16	22-01-1163
17	22-01-1173
18	22-01-1183
19	22-01-1193
20	22-01-1203