



*Material:

Insulator: PBT+Glass Fiber (UL94V-0).

Contact: Copper Alloy.

Contact Plated:

All material accord with ROHS.

*Specification: **Gold-Plated over Nickel**

Withstanding Voltage: AC 500V for 1 Minute.

Insulation Resistance: 100 MΩ Min. at DC 500V.

Contact Resistance: 1 Ω Max..

Operating Temperature: -40°C --- +105°C.

備注:

1.加反折為3件式，不加反折為2件式。

2."*"標記為重點檢驗尺寸;加括號尺寸為參考尺寸。

3.未標示公差之尺寸參考公差表。

Pos.	Dim. A	Dim. B	Dim. C	Dim. D	Dim. E	Dim. F
6	12.32	6.35	5.08	12.12	13.55	5.00
8	14.86	8.89	7.62	14.66	13.55	5.00
10	17.40	11.43	10.16	17.20	13.55	5.00
12	19.94	13.97	12.70	19.74	13.55	5.00
14	22.48	16.51	15.24	22.28	13.55	5.00
16	25.02	19.05	17.78	24.82	13.55	5.00
18	27.56	21.59	20.32	27.36	13.55	5.00
20	30.10	24.13	22.86	29.90	13.55	5.00
24	35.18	29.21	27.94	34.98	13.55	5.00
26	37.72	31.75	30.48	37.52	13.55	5.00
30	42.80	36.83	35.56	42.80	13.55	5.00
34	47.88	41.91	40.64	47.68	13.55	5.00
36	50.42	44.45	43.18	50.22	13.55	5.00
40	55.50	49.53	48.26	55.30	13.55	5.00
44	60.58	54.61	53.34	60.38	13.55	5.00
50	68.20	62.23	60.96	68.40	13.55	5.00
60	80.90	74.93	73.66	80.70	13.55	5.00
64	85.98	80.01	78.74	85.78	13.55	5.00

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X_s ±
X_s ±
.XX ±
.XXX ±
ANG ±



ORDER INFORMATION

F-C3-xx-LF
SERIES | LEADFREE
06~64WAY
THREE TYPE

DESCRIPTION: 2.54mm IDC Connector Single Contact/with Nose Type