



## SPECIFICATION

- 1. Rated Voltage .....12Vp-p Square Wave
- 2. Operating Voltage .....3~30Vp-p Square Wave
- 3. Max. Rated Current .....3mA/12Vp-p Square Wave/4KHz
- 4. Resonant Frequency .....4.0±0.5KHz
- 5. Min. Sound Pressure Level.....88dB/12p-p Square Wave/10cm
- 6. Capacitance at 100Hz.....15000pF±30%
- 7. Shell Material/Color ..... PA/Black
- 8. Operating Temperature .....-20~+80°C
- 9. Store Temperature .....-30~+100°C
- 10. Weight .....2.5g

No.	DESCRIPTION	APPROVED	DATE	<b>KEPO</b> NINGBO KEEP IMPROVING ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
TO: ENGINEER/INTEGRATOR	APPROVALS	DATE			
NO. OF ANGLES: XX	DRAWN				
XXX	CHECKED			UNIT	DWG NO.
90° ANGLES: XX	APPROVED			mm	KP3.840.269
FIRST ANGLE PROJECTION			03.01.16	SCALE	SHEET
					VER. 1.0