



<b>Symbol:</b>	NCDW-04
----------------	---------

<b>Manufacturer:</b>	NINIGI
----------------------	--------

## Product specifications

<b>Connector:</b>	socket
-------------------	--------

<b>Connector type:</b>	wire-board
------------------------	------------

<b>Connector type:</b>	male
------------------------	------

<b>Number of pins:</b>	4
------------------------	---

<b>Contacts pitch:</b>	2.54 mm
------------------------	---------

<b>Electrical mounting:</b>	THT
-----------------------------	-----

<b>Maximum current:</b>	2.5 A
-------------------------	-------

<b>Contact plating:</b>	tinned
-------------------------	--------

<b>Max. contact resistance::</b>	20 mΩ
----------------------------------	-------

<b>Flammability rating:</b>	UL94V-0
-----------------------------	---------

<b>Locking system:</b>	latch
<b>Operating temperature:</b>	-25...85 °C
<b>Type of pin configuration:</b>	1x4
<b>Max. operating voltage:</b>	250 V
<b>Spatial orientation:</b>	straight
<b>Enclosure material:</b>	polyamide
<b>A dimension:</b>	7.62 mm
<b>B dimension:</b>	12.71 mm

## Additional information

<b>Gross weight:</b>	0.001 kg
----------------------	----------