



- Up to 5.2 KV DC Isolation
- Short Circuit Protected
- 100 % Burn In

- Low Ripple and Noise
- Efficiency up to 78 %
- - 40°C to + 85°C

SIP12 - 1.5 W to 3 W Regulated

W	Series	INPUT (VDC)							Output	OUTPUT (VDC)										ISOLATION VDC	Material	
		3.3	5	9	12	15	24	48		3.3	3.6	4.8	5	7.2	9	12	15	18	24			
1.5	P8GGxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	1.000	P
1.5	P8GGxxxxEH30	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	3.000	P
1.5	P8GGxxxxEH52	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	5.200	P
2	P10GGxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	1.000	P
2	P10GGxxxxEH30	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	3.000	P
2	P10GGxxxxEH52	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	5.200	P
3	P14GGxxxxE	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	1.000	P
3	P14GGxxxxEH30	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	3.000	P
3	P14GGxxxxEH52	*	*	*	*	*	*	*	Single	*	*	*	*	*	*	*	*	*	*	*	5.200	P

WORLDWIDE DISTRIBUTION NETWORK

