

BC638; BCP52; BCX52

60 V, 1 A PNP medium power transistors

Rev. 06 — 29 March 2006

Product data sheet

1. Product profile

1.1 General description

PNP medium power transistor series.

Table 1: Product overview

Type number ^[1]	Package			NPN complement
	Philips	JEITA	JEDEC	
BC638 ^[2]	SOT54	SC-43A	TO-92	BC637
BCP52	SOT223	SC-73	-	BCP55
BCX52	SOT89	SC-62	TO-243	BCX55

[1] Valid for all available selection groups.

[2] Also available in SOT54A and SOT54 variant packages (see [Section 2](#)).

1.2 Features

- High current
- Two current gain selections

1.3 Applications

- Linear voltage regulators
- Low side switches
- Supply line switches
- MOSFET drivers

1.4 Quick reference data

Table 2: Quick reference data











Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{CEO}	collector-emitter voltage	open base	-	-	-60	V
I_C	collector current		-	-	-1	A
I_{CM}	peak collector current	single pulse; $t_p \leq 1$ ms	-	-	-1.5	A
h_{FE}	DC current gain	$V_{CE} = -2$ V; $I_C = -150$ mA	63	-	250	
	h_{FE} selection -10	$V_{CE} = -2$ V; $I_C = -150$ mA	63	-	160	
	h_{FE} selection -16	$V_{CE} = -2$ V; $I_C = -150$ mA	100	-	250	

PHILIPS



2. Pinning information

Table 3: Pinning

Pin	Description	Simplified outline	Symbol
SOT54			
1	base		
2	collector		
3	emitter		
SOT54A			
1	base		
2	collector		
3	emitter		
SOT54 variant			
1	base		
2	collector		
3	emitter		
SOT223			
1	base		
2	collector		
3	emitter		
4	collector		
SOT89			
1	emitter		
2	collector		
3	base		

3. Ordering information

Table 4: Ordering information

Type number ^[1]	Package		
	Name	Description	Version
BC638 ^[2]	SC-43A	plastic single-ended leaded (through hole) package; 3 leads	SOT54
BCP52	SC-73	plastic surface mounted package with increased heatsink; 4 leads	SOT223
BCX52	SC-62	plastic surface mounted package; collector pad for good heat transfer; 3 leads	SOT89

[1] Valid for all available selection groups.

[2] Also available in SOT54A and SOT54 variant packages (see [Section 2](#) and [Section 9](#)).

4. Marking

Table 5: Marking codes

Type number	Marking code
BC638	C638
BC638-16	C63816
BCP52	BCP52
BCP52-10	BCP52/10
BCP52-16	BCP52/16
BCX52	AE
BCX52-10	AG
BCX52-16	AM

5. Limiting values

Table 6: Limiting values


In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{CBO}	collector-base voltage	open emitter	-	-60	V
V_{CEO}	collector-emitter voltage	open base	-	-60	V
V_{EBO}	emitter-base voltage	open collector	-	-5	V
I_C	collector current		-	-1	A
I_{CM}	peak collector current	single pulse; $t_p \leq 1$ ms	-	-1.5	A
I_{BM}	peak base current	single pulse; $t_p \leq 1$ ms	-	-0.2	A
P_{tot}	total power dissipation	$T_{amb} \leq 25$ °C			
	BC638		[1] -	0.83	W
	BCP52		[1] -	0.65	W
			[2] -	1	W
	BCX52		[1] -	0.5	W
			[2] -	0.9	W
			[3] -	1.5	W
T_{stg}	storage temperature		-65	+150	°C
T_j	junction temperature		-	150	°C
T_{amb}	ambient temperature		-65	+150	°C

[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint.


[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1 cm².

[3] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 6 cm².




FR4 PCB; standard footprint

Fig 1. Power derating curve SOT54



FR4 PCB; standard footprint

Fig 2. Power derating curve SOT223



- (1) FR4 PCB; mounting pad for collector 6 cm²
- (2) FR4 PCB; mounting pad for collector 1 cm²
- (3) FR4 PCB; standard footprint

Fig 3. Power derating curves SOT89

6. Thermal characteristics


Table 7: Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air				
			[1]	-	-	150 K/W
			[1]	-	-	190 K/W
			[2]	-	-	125 K/W
			[1]	-	-	230 K/W
			[2]	-	-	135 K/W
			[3]	-	-	85 K/W
$R_{th(j-sp)}$	thermal resistance from junction to solder point					
			-	-	40	K/W
			-	-	17	K/W
			-	-	20	K/W

[1] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1 cm².


[3] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 6 cm².



FR4 PCB; standard footprint

- (1) $\delta = 1$
- (2) $\delta = 0.75$
- (3) $\delta = 0.5$
- (4) $\delta = 0.33$
- (5) $\delta = 0.2$
- (6) $\delta = 0.1$
- (7) $\delta = 0.05$
- (8) $\delta = 0.02$
- (9) $\delta = 0.01$
- (10) $\delta = 0$


Fig 4. Transient thermal impedance from junction to ambient as a function of pulse time for SOT54; typical values



FR4 PCB; standard footprint

- (1) $\delta = 1$
- (2) $\delta = 0.75$
- (3) $\delta = 0.5$
- (4) $\delta = 0.33$
- (5) $\delta = 0.2$
- (6) $\delta = 0.1$
- (7) $\delta = 0.05$
- (8) $\delta = 0.02$
- (9) $\delta = 0.01$
- (10) $\delta = 0$


Fig 5. Transient thermal impedance from junction to ambient as a function of pulse time for SOT223; typical values



FR4 PCB; standard footprint

- (1) $\delta = 1$
- (2) $\delta = 0.75$
- (3) $\delta = 0.5$
- (4) $\delta = 0.33$
- (5) $\delta = 0.2$
- (6) $\delta = 0.1$
- (7) $\delta = 0.05$
- (8) $\delta = 0.02$
- (9) $\delta = 0.01$
- (10) $\delta = 0$

Fig 6. Transient thermal impedance from junction to ambient as a function of pulse time for SOT89; typical values



FR4 PCB; mounting pad for collector 1 cm²

- (1) $\delta = 1$
- (2) $\delta = 0.75$
- (3) $\delta = 0.5$
- (4) $\delta = 0.33$
- (5) $\delta = 0.2$
- (6) $\delta = 0.1$
- (7) $\delta = 0.05$
- (8) $\delta = 0.02$
- (9) $\delta = 0.01$
- (10) $\delta = 0$


Fig 7. Transient thermal impedance from junction to ambient as a function of pulse time for SOT89; typical values

7. Characteristics

Table 8: Characteristics


$T_{amb} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
I_{CBO}	collector-base cut-off current	$V_{CB} = -30\text{ V}; I_E = 0\text{ A};$	-	-	-100	nA
		$V_{CB} = -30\text{ V}; I_E = 0\text{ A};$	-	-	-10	μA
		$T_j = 150\text{ }^{\circ}\text{C}$				
I_{EBO}	emitter-base cut-off current	$V_{EB} = -5\text{ V}; I_C = 0\text{ A}$	-	-	-100	nA
h_{FE}	DC current gain	$V_{CE} = -2\text{ V}$				
		$I_C = -5\text{ mA}$	63	-	-	
		$I_C = -150\text{ mA}$	63	-	250	
		$I_C = -500\text{ mA}$	40	-	-	
	DC current gain	$V_{CE} = -2\text{ V}$				
		$h_{FE}\text{ selection -10}$	63	-	160	
	$h_{FE}\text{ selection -16}$	$I_C = -150\text{ mA}$	100	-	250	
V_{CEsat}	collector-emitter saturation voltage	$I_C = -500\text{ mA};$ $I_B = -50\text{ mA}$	-	-	-0.5	V
V_{BE}	base-emitter voltage	$I_C = -500\text{ mA}; V_{CE} = -2\text{ V}$	-	-	-1	V
C_c	collector capacitance	$V_{CB} = -10\text{ V}; I_E = I_e = 0\text{ A};$ $f = 1\text{ MHz}$	-	15	-	pF
f_T	transition frequency	$V_{CE} = -5\text{ V}; I_C = -50\text{ mA};$ $f = 100\text{ MHz}$	-	145	-	MHz




$V_{CE} = -2 \text{ V}$
(1) $T_{amb} = 150 \text{ }^{\circ}\text{C}$
(2) $T_{amb} = 25 \text{ }^{\circ}\text{C}$
(3) $T_{amb} = -55 \text{ }^{\circ}\text{C}$

Fig 8. DC current gain as a function of collector current; typical values




$V_{CE} = -2 \text{ V}$
(1) $T_{amb} = -55 \text{ }^{\circ}\text{C}$
(2) $T_{amb} = 25 \text{ }^{\circ}\text{C}$
(3) $T_{amb} = 150 \text{ }^{\circ}\text{C}$

Fig 9. Base-emitter voltage as a function of collector current; typical values




$I_C/I_B = 10$
(1) $T_{amb} = 150 \text{ }^{\circ}\text{C}$
(2) $T_{amb} = 25 \text{ }^{\circ}\text{C}$
(3) $T_{amb} = -55 \text{ }^{\circ}\text{C}$

Fig 10. Collector-emitter saturation voltage as a function of collector current; typical values



$I_C/I_B = 10$
(1) $T_{amb} = 150 \text{ }^{\circ}\text{C}$
(2) $T_{amb} = 25 \text{ }^{\circ}\text{C}$
(3) $T_{amb} = -55 \text{ }^{\circ}\text{C}$






Fig 11. Collector-emitter saturation resistance as a function of collector current; typical values



$T_{amb} = 25\text{ }^{\circ}\text{C}$

- (1) $I_B = -45\text{ mA}$
- (2) $I_B = -40.5\text{ mA}$
- (3) $I_B = -36\text{ mA}$
- (4) $I_B = -31.5\text{ mA}$
- (5) $I_B = -27\text{ mA}$
- (6) $I_B = -22.5\text{ mA}$
- (7) $I_B = -18\text{ mA}$
- (8) $I_B = -13.5\text{ mA}$
- (9) $I_B = -9\text{ mA}$
- (10) $I_B = -4.5\text{ mA}$

Fig 12. Collector current as a function of collector-emitter voltage; typical values



9. Packing information

Table 9: Packing methods

The indicated -xxx are the last three digits of the 12NC ordering code. [\[1\]](#)

Type number [2]	Package	Description	Packing quantity			
			1000	4000	5000	10000
BC638	SOT54	bulk, straight leads	-	-	-412	-
	SOT54A	tape and reel, wide pitch	-	-	-	-116
		tape ammopack, wide pitch	-	-	-	-126
	SOT54 variant	bulk, delta pinning	-	-	-112	-
BCP52	SOT223	4 mm pitch, 12 mm tape and reel	-115	-135	-	-
BCX52	SOT89	8 mm pitch, 12 mm tape and reel	-115	-135	-	-

[1] For further information and the availability of packing methods, see [Section 15](#).

[2] Valid for all available selection groups.

10. Revision history

Table 10: Revision history

Document ID	Release date	Data sheet status	Change notice	Doc. number	Supersedes
BC638_BCP52_BCX52_6	20060329	Product data sheet	-	9397 750 14046	BC636_638_640_5 BCP51_52_53_5 BCX51_52_53_4
Modifications: - The format of this data sheet has been redesigned to comply with the new presentation and information standard of Philips Semiconductors. - This data sheet contains a type combination out of the previous data sheets BC636_638_640_5, BCP51_52_53_5 and BCX51_52_53_4. Table 1 "Product overview": added Figure 1, 2 and 3: added Table 7: amended typing error for BCP52 maximum value on 1 cm² footprint condition Figure 4, 5, 6 and 7: added Figure 8: amended Figure 9, 10, 11 and 12: added Figure 14 and 15: added Figure 13, 16 and 17: superseded by minimized package outline drawings Section 9 "Packing information": added Section 14 "Trademarks": added					
BC636_638_640_5	20041011	Product specification	-	9397 750 13575	BC636_638_640_4
BCP51_52_53_5	20030206	Product specification	-	9397 750 10764	BCP51_52_53_4
BCX51_52_53_4	20011010	Product specification	-	9397 750 08743	BCX51_52_53_3

11. Data sheet status

Level	Data sheet status ^[1]	Product status ^{[2] [3]}	Definition
I	Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
II	Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
III	Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN).

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

12. Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

14. Trademarks

Notice — All referenced brands, product names, service names and trademarks are the property of their respective owners.

13. Disclaimers

Life support — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors

15. Contact information

For additional information, please visit: <http://www.semiconductors.philips.com>

For sales office addresses, send an email to: sales.addresses@www.semiconductors.philips.com



16. Contents

1 Product profile 1

1.1 General description..... 1

1.2 Features 1

1.3 Applications 1

1.4 Quick reference data..... 1

2 Pinning information..... 2

3 Ordering information..... 3

4 Marking..... 3

5 Limiting values..... 4

6 Thermal characteristics..... 6

7 Characteristics..... 11

8 Package outline 14

9 Packing information..... 15

10 Revision history..... 16

11 Data sheet status 17

12 Definitions 17

13 Disclaimers..... 17

14 Trademarks..... 17

15 Contact information 17

