


**APPLICATIONS**

- SPEAKER
- BUZZER
- HEADPHONE

- MAGNETIC BUZZER
- TELEPHONE MIC
- GENERAL
- TELEPHONE RECEIVER

**SELECTION GUIDE FOR DYNAMIC TYPE**

Application	Model	SIZE		Sensitivity (dB)	Impedance (ohms)	W (g)	Remarks
		Diameter (mm)	Height (mm)				
	DH-51	31.0	12.2	99.0	300	18.6	-
	DH-51C	31.0	12.2	99.0	300	21.0	Hearing Aid Type
	DH-58	28.0	12.0	92.5	200	9.3	-
	*DH-60	35.0	18.0	96.0	150	32.8	-
	*DH-60C2	35.0	18.0	96.0	150	34.0	Hearing Aid Type
	*DH-60C3	35.0	18.0	96.0	150	35.6	-
	*DH-60C4	35.0	18.0	97.0	180	34.0	Hearing Aid Type
	*DH-60ES	35.0	18.0	96.0	300	34.0	Hearing Aid Type
	*DH-60ESA	35.0	18.0	96.0	300	34.0	HAC with Varistor
	DH-63C1	45.8	19.7	98.5	150	76.0	Hearing Aid Type
	DH-63C2	45.8	19.7	98.5	150	77.7	Hearing Aid Type
	DH-70	35.0	17.6	96.5	150	26.0	-
	DH-70C	35.0	17.6	95.0	150	27.5	Hearing Aid Type
	*DH-74	32.0	12.5	88.0	150	13.4	-
	DH-75	20.0	3.0	89.5	150	2.1	Flat Response
	DH-75D5	20.0	3.4	110.0	33	2.1	-
	DH-75D6	20.0	3.4	100.5	33.0	2.10	Flat Response
	DH-76	28.0	7.3	91.0	200	6.2	-

 <p>TELEPHONE RECEIVER</p>	DH-78	23.0	4.3	91.0	150	4.7	-
	DH-78D5	23.0	4.3	108.5	30	4.7	-
	DH-80	35.0	12.9	88.0	150	16.0	-
	DH-81	19.0	2.5	100.0	33	2.2	-
	DH-81D5	19.2	2.5	110.0	33	2.2	-
	DH-81D6	19.2	2.5	99.0	33.0	2.20	-
	DH-83A5	15.0	2.5	110.5	150	1.4	-
	DH-83D6	15.0	2.5	107.0	33	1.4	-
	DH-83D8	15.0	2.5	113.0/79.5	16.0	1.4	Used as Receiver or Speaker (Speaker:79.5dB)
	DH-85D5-X	15.0	2.5	108.0	33.0	1.42	Spring Contact
	DH-85D5A	15.0	2.5	108.5	33	1.4	-
	DH-85D6	15.0	2.5	108.0	33.0	1.34	-
	DH-86E	18.7	2.3	88.0	8.0	1.4	-
	DH-87D5	13.0	2.4	106.0	33.0	0.99	-
	DH-89	15.0	3.0	88.0	8.0	1.3	-
	DH-90/90X	14.8	3.0	88.0	11.0	1.3	Soldering/ Spring Contact
DH-91X	17.0	2.7	88.0	11.0	1.5	Spring Contact	
DH-100DX	15.0	2.5	96.0	33	1.4	With Spring	

\*Singapore Made



Copyright (C) 1998 Primo (Singapore)

Last updated:November 2002