


## QUAD EXCLUSIVE-OR GATE

- MEDIUM SPEED OPERATION -  $t_{pHL} = t_{pLH} = 65\text{ns}$  (TYP.) at  $C_L = 50\text{pF}$  and  $V_{DD} - V_{SS} = 10\text{V}$
- LOW OUTPUT IMPEDANCE :  $500\ \Omega$  (TYP.) at  $V_{DD} - V_{SS} = 10\text{V}$
- QUIESCENT CURRENT SPECIFIED UP TO  $20\text{V}$
- 5V, 10V AND 15V PARAMETRIC RATINGS
- INPUT LEAKAGE CURRENT  
 $I_I = 100\text{nA}$  (MAX) AT  $V_{DD} = 18\text{V}$   $T_A = 25^\circ\text{C}$
- 100% TESTED FOR QUIESCENT CURRENT
- MEETS ALL REQUIREMENTS OF JEDEC JESD13B "STANDARD SPECIFICATIONS FOR DESCRIPTION OF B SERIES CMOS DEVICES"




### ORDER CODES

| PACKAGE | TUBE       | T & R         |
|---------|------------|---------------|
| DIP     | HCF4030BEY |               |
| SOP     | HCF4030BM1 | HCF4030M013TR |


### DESCRIPTION

HCF4030B is a monolithic integrated circuit fabricated in Metal Oxide Semiconductor technology available in DIP and SOP packages. HCF4030B types consist of four independent exclusive-OR gates integrated on a single monolithic silicon chip. Each exclusive-OR gate consists of four n-channel and four p-channel enhancement-type transistors. All inputs and outputs are protected against electrostatic effects.

### PIN CONNECTION



INPUT EQUIVALENT CIRCUIT




PIN DESCRIPTION

| PIN No                   | SYMBOL                 | NAME AND FUNCTION       |
|--------------------------|------------------------|-------------------------|
| 2, 1, 5, 6, 8, 9, 12, 13 | A, B, C, D, E, F, G, H | Data Inputs             |
| 3, 4, 10, 11             | J, K, L, M             | Data Outputs            |
| 7                        | V <sub>SS</sub>        | Negative Supply Voltage |
| 14                       | V <sub>DD</sub>        | Positive Supply Voltage |

TRUTH TABLE

| IN1 | IN2 | OUT |
|-----|-----|-----|
| L   | L   | L   |
| L   | H   | H   |
| H   | L   | H   |
| H   | H   | L   |

FUNCTIONAL DIAGRAM



ABSOLUTE MAXIMUM RATINGS

| Symbol           | Parameter                               | Value                         | Unit |
|------------------|-----------------------------------------|-------------------------------|------|
| V <sub>DD</sub>  | Supply Voltage                          | -0.5 to +22                   | V    |
| V <sub>I</sub>   | DC Input Voltage                        | -0.5 to V <sub>DD</sub> + 0.5 | V    |
| I <sub>I</sub>   | DC Input Current                        | ± 10                          | mA   |
| P <sub>D</sub>   | Power Dissipation per Package           | 200                           | mW   |
|                  | Power Dissipation per Output Transistor | 100                           | mW   |
| T <sub>op</sub>  | Operating Temperature                   | -55 to +125                   | °C   |
| T <sub>stg</sub> | Storage Temperature                     | -65 to +150                   | °C   |

Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied.  
All voltage values are referred to V<sub>SS</sub> pin voltage.



## RECOMMENDED OPERATING CONDITIONS

| Symbol   | Parameter             | Value         | Unit |
|----------|-----------------------|---------------|------|
| $V_{DD}$ | Supply Voltage        | 3 to 20       | V    |
| $V_I$    | Input Voltage         | 0 to $V_{DD}$ | V    |
| $T_{op}$ | Operating Temperature | -55 to 125    | °C   |

## DC SPECIFICATIONS


| Symbol          | Parameter             | Test Condition        |                       |                          |                        | Value                 |                   |      |             |      |              |      | Unit |
|-----------------|-----------------------|-----------------------|-----------------------|--------------------------|------------------------|-----------------------|-------------------|------|-------------|------|--------------|------|------|
|                 |                       | V <sub>I</sub><br>(V) | V <sub>O</sub><br>(V) | I <sub>O</sub>  <br>(μA) | V <sub>DD</sub><br>(V) | T <sub>A</sub> = 25°C |                   |      | -40 to 85°C |      | -55 to 125°C |      |      |
|                 |                       |                       |                       |                          |                        | Min.                  | Typ.              | Max. | Min.        | Max. | Min.         | Max. |      |
| I <sub>L</sub>  | Quiescent Current     | 0/5                   |                       |                          | 5                      |                       | 0.02              | 4    |             | 4    |              | 30   | μA   |
|                 |                       | 0/10                  |                       |                          | 10                     |                       | 0.02              | 8    |             | 8    |              | 60   |      |
|                 |                       | 0/15                  |                       |                          | 15                     |                       | 0.02              | 16   |             | 16   |              | 120  |      |
|                 |                       | 0/20                  |                       |                          | 20                     |                       | 0.04              | 20   |             | 20   |              | 600  |      |
| V <sub>OH</sub> | Output High Voltage   | 0/5                   |                       | <1                       | 5                      | 4.95                  |                   |      | 4.95        |      | 4.95         |      | V    |
|                 |                       | 0/10                  |                       | <1                       | 10                     | 9.95                  |                   |      | 9.95        |      | 9.95         |      |      |
|                 |                       | 0/15                  |                       | <1                       | 15                     | 14.95                 |                   |      | 14.95       |      | 14.95        |      |      |
| V <sub>OL</sub> | Output Low Voltage    | 5/0                   |                       | <1                       | 5                      |                       | 0.05              |      |             | 0.05 |              | 0.05 | V    |
|                 |                       | 10/0                  |                       | <1                       | 10                     |                       | 0.05              |      |             | 0.05 |              | 0.05 |      |
|                 |                       | 15/0                  |                       | <1                       | 15                     |                       | 0.05              |      |             | 0.05 |              | 0.05 |      |
| V <sub>IH</sub> | Input High Voltage    |                       | 0.5/4.5               | <1                       | 5                      | 3.5                   |                   |      | 3.5         |      | 3.5          |      | V    |
|                 |                       |                       | 1/9                   | <1                       | 10                     | 7                     |                   |      | 7           |      | 7            |      |      |
|                 |                       |                       | 1.5/13.5              | <1                       | 15                     | 11                    |                   |      | 11          |      | 11           |      |      |
| V <sub>IL</sub> | Input Low Voltage     |                       | 4.5/0.5               | <1                       | 5                      |                       |                   | 1.5  |             | 1.5  |              | 1.5  | V    |
|                 |                       |                       | 9/1                   | <1                       | 10                     |                       |                   | 3    |             | 3    |              | 3    |      |
|                 |                       |                       | 13.5/1.5              | <1                       | 15                     |                       |                   | 4    |             | 4    |              | 4    |      |
| I <sub>OH</sub> | Output Drive Current  | 0/5                   | 2.5                   | <1                       | 5                      | -1.36                 | -3.2              |      | -1.15       |      | -1.1         |      | mA   |
|                 |                       | 0/5                   | 4.6                   | <1                       | 5                      | -0.44                 | -1                |      | -0.36       |      | -0.36        |      |      |
|                 |                       | 0/10                  | 9.5                   | <1                       | 10                     | -1.1                  | -2.6              |      | -0.9        |      | -0.9         |      |      |
|                 |                       | 0/15                  | 13.5                  | <1                       | 15                     | -3.0                  | -6.8              |      | -2.4        |      | -2.4         |      |      |
| I <sub>OL</sub> | Output Sink Current   | 0/5                   | 0.4                   | <1                       | 5                      | 0.44                  | 1                 |      | 0.36        |      | 0.36         |      | mA   |
|                 |                       | 0/10                  | 0.5                   | <1                       | 10                     | 1.1                   | 2.6               |      | 0.9         |      | 0.9          |      |      |
|                 |                       | 0/15                  | 1.5                   | <1                       | 15                     | 3.0                   | 6.8               |      | 2.4         |      | 2.4          |      |      |
| I <sub>I</sub>  | Input Leakage Current | 0/18                  | Any Input             |                          | 18                     |                       | ±10 <sup>-5</sup> | ±0.1 |             | ±1   |              | ±1   | μA   |
| C <sub>I</sub>  | Input Capacitance     |                       | Any Input             |                          |                        |                       | 5                 | 7.5  |             |      |              |      | pF   |

The Noise Margin for both "1" and "0" level is: 1V min. with  $V_{DD}=5V$ , 2V min. with  $V_{DD}=10V$ , 2.5V min. with  $V_{DD}=15V$


DYNAMIC ELECTRICAL CHARACTERISTICS ( $T_{amb} = 25^\circ C$ ,  $C_L = 50pF$ ,  $R_L = 200K\Omega$ ,  $t_r = t_f = 20 ns$ )

| Symbol              | Parameter              | Test Condition |  | Value (*) |      |      | Unit |
|---------------------|------------------------|----------------|--|-----------|------|------|------|
|                     |                        | $V_{DD}$ (V)   |  | Min.      | Typ. | Max. |      |
| $t_{PLH}$ $t_{PHL}$ | Propagation Delay Time | 5              |  |           | 140  | 280  | ns   |
|                     |                        | 10             |  |           | 65   | 130  |      |
|                     |                        | 15             |  |           | 50   | 100  |      |
| $t_{TLH}$ $t_{THL}$ | Output Transition Time | 5              |  |           | 100  | 200  | ns   |
|                     |                        | 10             |  |           | 50   | 100  |      |
|                     |                        | 15             |  |           | 40   | 80   |      |


## TYPICAL APPLICATION : EVEN PARITY-BIT GENERATOR




## TYPICAL APPLICATION : EVEN PARITY-CHECKER




## TYPICAL APPLICATION : ODD-PARITY-BIT GENERATOR




## TYPICAL APPLICATION : ODD-PARITY-CHECKER



## TYPICAL APPLICATION : 8-BIT COMPARATOR




**TYPICAL APPLICATION : 8-BIT TWO'S COMPLEMENT ADDER-SUBTRACTOR**




(\*) Typical temperature coefficient for all  $V_{DD}$  value is 0.3 %/°C.

**TEST CIRCUIT**




$C_L$  = 50pF or equivalent (includes jig and probe capacitance)  
 $R_L$  = 200K $\Omega$   
 $R_T$  =  $Z_{OUT}$  of pulse generator (typically 50 $\Omega$ )

**WAVEFORM : PROPAGATION DELAY TIMES ( $f=1\text{MHz}$ ; 50% duty cycle)**

CS08770

## Plastic DIP-14 MECHANICAL DATA


| DIM. | mm.  |       |      | inch  |       |       |
|------|------|-------|------|-------|-------|-------|
|      | MIN. | TYP   | MAX. | MIN.  | TYP.  | MAX.  |
| a1   | 0.51 |       |      | 0.020 |       |       |
| B    | 1.39 |       | 1.65 | 0.055 |       | 0.065 |
| b    |      | 0.5   |      |       | 0.020 |       |
| b1   |      | 0.25  |      |       | 0.010 |       |
| D    |      |       | 20   |       |       | 0.787 |
| E    |      | 8.5   |      |       | 0.335 |       |
| e    |      | 2.54  |      |       | 0.100 |       |
| e3   |      | 15.24 |      |       | 0.600 |       |
| F    |      |       | 7.1  |       |       | 0.280 |
| I    |      |       | 5.1  |       |       | 0.201 |
| L    |      | 3.3   |      |       | 0.130 |       |
| Z    | 1.27 |       | 2.54 | 0.050 |       | 0.100 |



P001A

## SO-14 MECHANICAL DATA

| DIM. | mm.        |      |      | inch  |       |       |
|------|------------|------|------|-------|-------|-------|
|      | MIN.       | TYP  | MAX. | MIN.  | TYP.  | MAX.  |
| A    |            |      | 1.75 |       |       | 0.068 |
| a1   | 0.1        |      | 0.2  | 0.003 |       | 0.007 |
| a2   |            |      | 1.65 |       |       | 0.064 |
| b    | 0.35       |      | 0.46 | 0.013 |       | 0.018 |
| b1   | 0.19       |      | 0.25 | 0.007 |       | 0.010 |
| C    |            | 0.5  |      |       | 0.019 |       |
| c1   | 45° (typ.) |      |      |       |       |       |
| D    | 8.55       |      | 8.75 | 0.336 |       | 0.344 |
| E    | 5.8        |      | 6.2  | 0.228 |       | 0.244 |
| e    |            | 1.27 |      |       | 0.050 |       |
| e3   |            | 7.62 |      |       | 0.300 |       |
| F    | 3.8        |      | 4.0  | 0.149 |       | 0.157 |
| G    | 4.6        |      | 5.3  | 0.181 |       | 0.208 |
| L    | 0.5        |      | 1.27 | 0.019 |       | 0.050 |
| M    |            |      | 0.68 |       |       | 0.026 |
| S    | 8° (max.)  |      |      |       |       |       |



PO13G

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a registered trademark of STMicroelectronics

© 2002 STMicroelectronics - Printed in Italy - All Rights Reserved  
STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco  
Singapore - Spain - Sweden - Switzerland - United Kingdom - United States.

© <http://www.st.com>