

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

ALL RIGHTS RESERVED.

By -

LOC

DIST

CM

00

REVISED PER

ECO-11-014381

DATE

12OCT11

DWN

KH

APVD

SM

1

POST TO WITHSTAND 13 NEWTONS (3 LBS) MINIMUM AXIAL FORCE IN BOTH DIRECTIONS SHOWN WITHOUT DISLODGING.

2

TOLERANCES APPLY TO SOLDER SIDE OF BOARD.

3

MEASURED

ATA-

4

PLASTIC FLASH PERMITTED IN THIS AREA.

5

PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-2.

6

ONE HOLE MAY BE UNDERSIZED 0.81-0.89 [.032-.035] DIA. FOR ASSEMBLY RETENTION DURING WAVE SOLDERING.

7

MATERIAL: HEADER-THERMOPLASTIC POLYESTER
94V-0 (NATURAL)
POST-COPPER ALLOY
FINISH-USE PLATING NOTES 13 & 14 FOR -2 THRU -28
AND NOTES 13 & 15 FOR -32 THRU -58

8

COORDINATE DIMENSION APPLIES FROM CENTER OF ACTUAL FEATURE.

9

PLASTIC BURRS CAUSED BY CUT-OFF TOOLING ARE PERMITTED WITHIN THE MAXIMUM TOLERANCE ENVELOPE.

10

POSTS TO BE MEASURED WHEN STRIP IS HELD FLAT.

11

POST MUST WITHSTAND TWO 90° BENDS AGAINST EXTRUSION WITHOUT BREAKING.

12

DIMENSION SHOULD BE 3.30 [.130] MIN WHEN MATING WITH A MTA-100 CONNECTOR ASSEMBLY OR A CST-100 CONNECTOR ASSEMBLY.

13

PLATING: GOLD PLATE AREA, 0.00038 [.000015] GOLD OR 0.00008 [.000003] MIN GOLD FLASH OVER 0.00030 [.000012] PALLADIUM NICKEL, PER TE CONNECTIVITY'S DISCRETION, ALL SIDES, OVER NICKEL UNDERPLATE, 0.00127 [.000050] MIN, ALL SIDES AND ENTIRE LENGTH OF POST.

14

PLATING: BRIGHT TIN/LEAD (93/7) PLATE AREA, 0.00381-0.00889 [.000150-.000350] THICK, ALL FOUR SIDES 3.56 [.140] MINIMUM.

15

PLATING: MATTE TIN PLATE AREA,0.00381-0.00889 [.000150-.000350] THICK, ALL FOUR SIDES 3.56 [.140] MINIMUM.

16

OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

5.72±0.25
[.225±.010]

0.25/25.40
.010/1.000

3.17
[.125]

3

0.63±0.03
[.025±.001]
SQUARE

0.25 [.010] A
0.20 [.008] M

10 3
10

TYP

1

TYP

13.59±0.25
[.535±.010]

7.49
[.295]

6.60
[.260]
MIN

1.02 [.040]
0.38 [.015]

11

7.87±0.38
[.310±.015]

0.51
[.020]
MAX

4

3.56±0.38
[.140±.015]

14 15

2.54±0.20
[.100±.008]

0.25/25.40
.010/1.000

1.27±0.20
[.050±.008]
TYP

8

2.54
[.100]
TYP

1

TYP

2.54
[.100]
TYP

EDGE OF BOARD

1.02±0.25
-0.00
0.010
0.000

0.040±.010
0.000

6

0.25 [.010] M

12

RECOMMENDED MOUNTING HOLE PATTERN FOR 1.60 [.063] THICK P.C. BOARD

2

71.12 [2.800]

68.58 [2.700]

66.04 [2.600]

63.50 [2.500]

60.96 [2.400]

58.42 [2.300]

55.88 [2.200]

53.34 [2.100]

50.80 [2.000]

48.26 [1.900]

45.72 [1.800]

43.18 [1.700]

40.64 [1.600]

38.10 [1.500]

35.56 [1.400]

33.02 [1.300]

30.48 [1.200]

27.94 [1.100]

25.40 [1.000]

22.86 [.900]

20.32 [.800]

17.78 [.700]

15.24 [.600]

12.70 [.500]

10.16 [.400]

7.62 [.300]

5.08 [.200]

DIM (L)

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

NO.OF POSN

5-641126-8

5-641126-7

5-641126-6

5-641126-5

5-641126-4

5-641126-3

5-641126-2

5-641126-1

5-641126-0

4-641126-9

4-641126-8

4-641126-7

4-641126-6

4-641126-5

4-641126-4

4-641126-3

4-641126-2

4-641126-1

4-641126-0

3-641126-9

3-641126-8

3-641126-7

3-641126-6

3-641126-5

3-641126-4

3-641126-3

3-641126-2

ASSEMBLY

71.12 [2.800]

68.58 [2.700]

66.04 [2.600]

63.50 [2.500]

60.96 [2.400]

58.42 [2.300]

55.88 [2.200]

53.34 [2.100]

50.80 [2.000]

48.26 [1.900]

45.72 [1.800]

43.18 [1.700]

40.64 [1.600]

38.10 [1.500]

35.56 [1.400]

33.02 [1.300]

30.48 [1.200]

27.94 [1.100]

25.40 [1.000]

22.86 [.900]

20.32 [.800]

17.78 [.700]

15.24 [.600]

12.70 [.500]

10.16 [.400]

7.62 [.300]

5.08 [.200]

DIM (L)

28

27

26

25

24

23

22

21

20

19

18

17

16

15

14

13

12

11

10

9

8

7

6

5

4

3

2

NO.OF POSN

2-641126-8

2-641126-7

2-641126-6

2-641126-5

2-641126-4

2-641126-3

2-641126-2

2-641126-1

2-641126-0

1-641126-9

1-641126-8

1-641126-7

1-641126-6

1-641126-5

1-641126-4

1-641126-3

1-641126-2

1-641126-1

1-641126-0

641126-9

641126-8

641126-7

641126-6

641126-5

641126-4

641126-3

641126-2

ASSEMBLY

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN S. HOOVER 26-JAN-2005

CHK D. BOSSI 26-JAN-2005

APVD D. BOSSI 26-JAN-2005

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ±

1 PLC ±

2 PLC ±

3 PLC ±

4 PLC ±

ANGLES ±

FINISH ±

MATERIAL 7

7

WEIGHT

CUSTOMER DRAWING

APPLICATION SPEC

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

NAME

MTA-100 HEADER ASSEMBLY, FRICTION LOCK, NOTCHED, .025 SQUARE STRAIGHT POST, .000015 GOLD PLATED

REV

Z

TE Connectivity

MTA-100 HEADER ASSEMBLY, FRICTION LOCK, NOTCHED, .025 SQUARE STRAIGHT POST, .000015 GOLD PLATED

100779

641126

8:1

1

1

REV

Z

METRIC

4805 (3/11)