


Wet Tantalum HI TMP[®] Capacitors Tantalum-Case with Glass-to-Tantalum Hermetic Seal for - 55 °C to + 200 °C Operation



FEATURES

Vishay 134D HI TMP[®] represents a major breakthrough in wet tantalum capacitor technology for high temperature (+ 200 °C) applications such as that seen in the petroleum exploration industry. Its unique design provides for the highest capacitance per unit volume. The design facilitates a doubling of capacitance when compared with conventional wet tantalum products.

The 134D is housed in an all tantalum, hermetically sealed case and is manufactured to withstand high stress and hazardous environments.

- Terminations: standard tin/lead (SnPb)
- 100 % tin (RoHS compliant) available
- Compliant to RoHS directive 2002/95/EC



RoHS*
COMPLIANT

PERFORMANCE CHARACTERISTICS

Operating Temperature: - 55 °C to + 85 °C (to + 200 °C with voltage derating)

Capacitance Tolerance: At 120 Hz, + 25 °C; ± 20 % standard; ± 10 %

DC Leakage Current (DCL Max.): At + 25 °C and above: Leakage current shall not exceed the values listed in the Standard Ratings tables.

Life Test: Capacitors are capable of withstanding a 500 h life test at a temperature of + 200 °C at the applicable derated DC working voltage.


ORDERING INFORMATION						
134D	227	X0	100	K	6	E3
TYPE	CAPACITANCE	CAPACITANCE TOLERANCE	DC VOLTAGE RATING AT + 85 °C	CASE CODE	STYLE NUMBER	RoHS COMPLIANT
	This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow	X0 = ± 20 % X9 = ± 10 %	This is expressed in volts. To complete the three-digit block, zeros precede the voltage rating. A decimal point is indicated by an "R" (6R3 = 6.3 V)	See Ratings and Case Codes table	High Temperature 8 = No outer insulating sleeve 6 = High temperature film insulation (above + 125 °C)	E3 = 100 % tin termination (RoHS compliant design) Blank = SnPb termination (standard design)

Note

Packaging: The use of formed plastic trays for packaging this type of axial lead component is standard. Tape and reel is not recommended due to the unit weight.

* Pb containing terminations are not RoHS compliant, exemptions may apply

Wet Tantalum HI TMP® Capacitors
Tantalum-Case with Glass-to-Tantalum Hermetic Seal
for - 55 °C to + 200 °C Operation

**DIMENSIONS** in inches [millimeters]

CASE CODE		D	L ₁	L ₂ (Max.)	E	WEIGHT (g) (Max.)
TYPE 134D	CLR 79/81 EQUIV.					
C	T1	0.188 ± 0.016 [4.78 ± 0.41]	0.453 + 0.031 - 0.016 [11.51 + 0.79 - 0.41]	0.734 [18.64]	1.500 ± 0.250 [38.10 ± 6.35]	2.6
F	T2	0.281 ± 0.016 [7.14 ± 0.41]	0.641 + 0.031 - 0.016 [16.28 + 0.79 - 0.41]	0.922 [23.42]	2.250 ± 0.250 [57.15 ± 6.35]	6.2
T	T3	0.375 ± 0.016 [9.53 ± 0.41]	0.766 + 0.031 - 0.016 [19.46 + 0.79 - 0.41]	1.047 [26.59]	2.250 ± 0.250 [57.15 ± 6.35]	11.6
K	T4	0.375 ± 0.016 [9.53 ± 0.41]	1.062 + 0.031 - 0.016 [26.97 + 0.79 - 0.41]	1.343 [34.11]	2.250 ± 0.250 [57.15 ± 6.35]	17.7

STANDARD RATINGS

CAPACITANCE AT 25 °C AND 120 Hz	CASE CODE	MAX. 120 Hz ESR Ω	MAX. DCL (μA) AT		MAXIMUM		TYPICAL				AC RIPPLE ⁽¹⁾ 85 °C 40 kHz mA rms
			25 °C	85 °C AND 125 °C	IMP, Z AT - 25 °C Ω	ΔCAP. AT - 25 °C	IMP, Z AT - 55 °C Ω	ΔCAP. AT - 55 °C %	ΔCAP. + 85 °C %	ΔCAP. + 125 °C %	
50 WVDC AT 85 °C ... 30 WVDC AT 125 °C ... 30 WVDC AT 200 °C											
68	C	1.50	1	5	22	- 6 %	25	- 11 %	12 %	55 %	1400
220	F	0.90	2	10	9	- 15 %	10	- 25 %	13 %	50 %	2300
470	T	0.75	3	25	6	- 24 %	8	- 50 %	10 %	25 %	2650
680	K	0.70	5	40	4	- 22 %	5	- 40 %	12 %	40 %	2900
60 WVDC AT 85 °C ... 40 WVDC AT 125 °C ... 36 WVDC AT 200 °C											
47	C	2.00	1	5	34	- 8 %	40	- 20 %	8 %	12 %	1250
150	F	1.10	2	10	13	- 11 %	15	- 25 %	10 %	30 %	2050
390	T	0.90	3	25	7	- 27 %	10	- 50 %	10 %	25 %	2450
560	K	0.80	5	40	5	- 21 %	6	- 40 %	12 %	40 %	2700
75 WVDC AT 85 °C ... 50 WVDC AT 125 °C ... 45 WVDC AT 200 °C											
33	C	2.50	1	5	45	- 3.5 %	50	- 6 %	8 %	25 %	1100
110	F	1.30	2	10	16	- 8 %	20	- 18 %	8 %	30 %	1900
330	T	1.00	3	30	8	- 30 %	12	- 50 %	10 %	25 %	2300
470	K	0.90	5	50	6	- 20 %	7	- 40 %	10 %	40 %	2550
100 WVDC AT 85 °C ... 65 WVDC AT 125 °C ... 60 WVDC AT 200 °C											
15	C	3.50	1	5	95	- 2.5 %	100	- 4 %	8 %	25 %	950
68	F	2.10	2	10	25	- 6 %	30	- 14 %	8 %	25 %	1500
150	T	1.60	3	25	14	- 12 %	18	- 30 %	8 %	22 %	1800
220	K	1.20	5	50	13	- 44 %	16	- 55 %	8 %	15 %	2200
125 WVDC AT 85 °C ... 85 WVDC AT 125 °C ... 75 WVDC AT 200 °C											
10	C	5.50	1	5	145	- 2.5 %	150	- 4 %	8 %	20 %	750
47	F	2.30	2	10	35	- 5 %	40	- 12 %	7 %	20 %	1450
50	F	2.30	3	10	35	- 5 %	40	- 12 %	7 %	20 %	1450
100	T	1.80	3	25	24	- 20 %	30	- 35 %	8 %	20 %	1700
150	K	1.60	5	50	13	- 10 %	16	- 28 %	6 %	12 %	1900

Note

⁽¹⁾ For insulated parts, add 0.015 inches [0.38] to the diameter. The insulation shall lap over the ends of the capacitor body.



Wet Tantalum HI TMP® Capacitors
 Tantalum-Case with Glass-to-Tantalum Hermetic Seal
 for - 55 °C to + 200 °C Operation

Vishay Sprague

EXTENDED RATINGS											
CAPACITANCE AT 25 °C AND 120 Hz	CASE CODE	MAX. 120 Hz ESR Ω	MAX. DCL μA		MAXIMUM			TYPICAL			AC RIPPLE (1) 85 °C 40 kHz mA rms
			25 °C	85 °C AND 125 °C	IMP, Z AT - 25 °C Ω	ΔCAP. AT - 25 °C	IMP, Z AT - 55 °C Ω	ΔCAP. AT - 55 °C %	ΔCAP. + 85 °C %	ΔCAP. + 125 °C %	
50 WVDC AT 85 °C ... 30 WVDC AT 125 °C ... 30 WVDC AT 200 °C											
	C F T K										
60 WVDC AT 85 °C ... 40 WVDC AT 125 °C ... 36 WVDC AT 200 °C											
	C F T K										
1000	K		<i>Preliminary rating</i>				<i>Contact marketing for information</i>				
75 WVDC AT 85 °C ... 50 WVDC AT 125 °C ... 45 WVDC AT 200 °C											
180	C F T K	1.50	5	25			30	- 35	+ 15	+ 20	2000
750	K		<i>Preliminary rating</i>				<i>Contact marketing for information</i>				
100 WVDC AT 85 °C ... 65 WVDC AT 125 °C ... 60 WVDC AT 200 °C											
	C F T K										
400	K	0.70	10	120	5	- 15	15	- 55	10	15	3250
125 WVDC AT 85 °C ... 85 WVDC AT 125 °C ... 75 WVDC AT 200 °C											
	C F T K										



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.