




Small Signal Switching Diodes, High Voltage

Features

- Silicon Epitaxial Planar Diodes
- For general purpose
- These diodes are also available in other case styles including: the DO-35 case with the type designations BAV19 to BAV21, the MiniMELF case with the type designations BAV100 to BAV103, the SOT-23 case with the type designations BAS19 to BAS21, and the SOD-323 case with type designations BAV19WS-V to BAV21WS-V.
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



17431

Mechanical Data

Case: SOD-123 Plastic case

Weight: approx. 9.3 mg

Packaging Codes/Options:

GS18 / 10 k per 13" reel (8 mm tape), 10 k/box

GS08 / 3 k per 7" reel (8 mm tape), 15 k/box

Parts Table

Part	Type differentiation	Ordering code	Marking	Remarks
BAV19W-V	$V_R = 100\text{ V}$	BAV19W-V-GS18 or BAV19W-V-GS08	A8	Tape and Reel
BAV20W-V	$V_R = 150\text{ V}$	BAV20W-V-GS18 or BAV20W-V-GS08	A9	Tape and Reel
BAV21W-V	$V_R = 200\text{ V}$	BAV21W-V-GS18 or BAV21W-V-GS08	AA	Tape and Reel

Absolute Maximum Ratings

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Test condition	Part	Symbol	Value	Unit
Continuous reverse voltage		BAV19W-V	V_R	100	V
		BAV20W-V	V_R	150	V
		BAV21W-V	V_R	200	V
Repetitive peak voltage		BAV19W-V	V_{RRM}	120	V
		BAV20W-V	V_{RRM}	200	V
		BAV21W-V	V_{RRM}	250	V
DC Forward current	$T_{amb} = 25\text{ }^{\circ}\text{C}$		I_F	250 ¹⁾	mA
Rectified current (average) half wave rectification with resist. load	$T_{amb} = 25\text{ }^{\circ}\text{C}$		$I_{F(AV)}$	200 ¹⁾	mA
Repetitive peak forward current	$f \geq 50\text{ Hz}$, $\theta = 180\text{ }^{\circ}$, $T_{amb} = 25\text{ }^{\circ}\text{C}$		I_{FRM}	625 ¹⁾	mA
Surge forward current	$t < 1\text{ s}$, $T_j = 25\text{ }^{\circ}\text{C}$		I_{FSM}	1	A
Power dissipation	$T_{amb} = 25\text{ }^{\circ}\text{C}$		P_{tot}	410 ¹⁾	mW

1) Valid provided that leads are kept at ambient temperature

Thermal Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified

Parameter	Test condition	Symbol	Value	Unit
Thermal resistance junction to ambient air		R_{thJA}	375 ¹⁾	$^{\circ}\text{C/W}$
Junction temperature		T_j	150 ¹⁾	$^{\circ}\text{C}$
Storage temperature range		T_S	- 65 to + 150 ¹⁾	$^{\circ}\text{C}$


1) Valid provided that leads are kept at ambient temperature

Electrical Characteristics

$T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified


Parameter	Test condition	Part	Symbol	Min	Typ.	Max	Unit
Forward voltage	$I_F = 100\text{ mA}$		V_F			1.00	V
	$I_F = 200\text{ mA}$		V_F			1.25	V
Leakage current	$V_R = 100\text{ V}$	BAV19W-V	I_R			100	nA
	$V_R = 100\text{ V}$, $T_j = 100\text{ }^{\circ}\text{C}$	BAV19W-V	I_R			15	μA
	$V_R = 150\text{ V}$	BAV20W-V	I_R			100	nA
	$V_R = 150\text{ V}$, $T_j = 100\text{ }^{\circ}\text{C}$	BAV20W-V	I_R			15	μA
	$V_R = 200\text{ V}$	BAV21W-V	I_R			100	nA
	$V_R = 200\text{ V}$, $T_j = 100\text{ }^{\circ}\text{C}$	BAV21W-V	I_R			15	μA
Dynamic forward resistance	$I_F = 10\text{ mA}$		r_f		5		Ω
Diode capacitance	$V_R = 0$, $f = 1\text{ MHz}$		C_{tot}		1.5		pF
Reverse recovery time	$I_F = 30\text{ mA}$, $I_R = 30\text{ mA}$, $I_{rr} = 3\text{ mA}$, $R_L = 100\text{ }\Omega$		t_{rr}			50	ns

Typical Characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)




18858

Figure 1. Forward Current vs. Forward Voltage




18861

Figure 4. Dynamic Forward Resistance vs. Forward Current




18859

Figure 2. Admissible Forward Current vs. Ambient Temperature




18862

Figure 5. Leakage Current vs. Junction Temperature



18860

Figure 3. Admissible Power Dissipation vs. Ambient Temperature



18863


Figure 6. Capacitance vs. Reverse Voltage

BAV19W-V / 20W-V / 21W-V



Vishay Semiconductors

Package Dimensions in mm (Inches)



17432



Ozone Depleting Substances Policy Statement

It is the policy of Vishay Semiconductor GmbH to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

We reserve the right to make changes to improve technical design and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.