


Case Style GP10E

Glass Passivated Junction Fast Switching Rectifier

Reverse Voltage 1200 to 2000V
Forward Current 0.5A

Patented*



Dimensions in inches and (millimeters)

* Glass-plastic encapsulation technique is covered by Patent No. 3,996,602, and brazed-lead assembly by Patent No. 3,930,306

Features

- Plastic package has Underwriters Laboratories Flammability Classification 94V-0
- High temperature metallurgically bonded construction
- Capable of meeting environmental standards of MIL-S-19500
- For use in high frequency rectifier circuits
- Fast switching for high efficiency
- Cavity-free glass passivated junction
- 0.5 Ampere operation at $T_A=55^\circ\text{C}$ with no thermal runaway
- Typical I_R less than $0.2\mu\text{A}$
- High temperature soldering guaranteed: $350^\circ\text{C}/10$ seconds, $0.375"$ (9.5mm) lead length, 5 lbs. (2.3kg) tension

Mechanical Data

Case: Molded plastic over glass body
Terminals: Plated axial leads, solderable per MIL-STD-750, Method 2026
Polarity: Color band denotes cathode end
Mounting Position: Any
Weight: 0.012 oz., 0.3 g

Maximum Ratings & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

| Parameter | Symbols | RGP02 -12E | RGP02 -14E | RGP02 -16E | RGP02 -18E | RGP02 -20E | Units |
|--|------------------------------------|-------------|------------|------------|------------|------------|--------------------|
| Maximum repetitive peak reverse voltage | VRRM | 1200 | 1400 | 1600 | 1800 | 2000 | V |
| Maximum RMS voltage | VRMS | 840 | 980 | 1120 | 1260 | 1400 | V |
| Maximum DC blocking voltage | VDC | 1200 | 1400 | 1600 | 1800 | 2000 | V |
| Maximum average forward rectified current 0.375" (9.5mm) lead length at $T_A=55^\circ\text{C}$ | $I_{F(AV)}$ | 0.5 | | | | | A |
| Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method) | I_{FSM} | 20 | | | | | A |
| Typical thermal resistance ⁽¹⁾ | $R_{\theta JA}$ $R_{\theta JL}$ | 65 30 | | | | | $^\circ\text{C/W}$ |
| Operating junction and storage temperature range | T_J, T_{STG} | -65 to +175 | | | | | $^\circ\text{C}$ |

Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

| | | | | | | | |
|---|----------|-----------|--|--|--|--|---------------|
| Maximum instantaneous forward voltage at 0.1A | V_F | 1.8 | | | | | V |
| Maximum DC reverse current at rated DC blocking voltage $T_A=25^\circ\text{C}$ $T_A=125^\circ\text{C}$ | I_R | 5.0 50 | | | | | μA |
| Maximum reverse recovery time at $I_F=0.5\text{A}, I_R=1.0\text{A}, I_{rr}=0.25\text{A}$ | t_{rr} | 300 | | | | | ns |
| Typical junction capacitance at 4.0V, 1MHz | C_J | 5.0 | | | | | pF |

Note:

(1) Thermal resistance from junction to ambient and from junction to lead at 0.375" (9.5mm) lead length, P.C.B. mounted

Vishay Semiconductors
formerly General Semiconductor

Ratings and Characteristic Curves (T_A = 25°C unless otherwise noted)

Fig. 1 — Forward Current Derating Curve




Fig. 2 — Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 — Typical Instantaneous Forward Characteristics




Fig. 4 — Typical Reverse Characteristics




Fig. 5 — Typical Junction Capacitance

