



P-Channel 2.5-V (G-S) MOSFET


PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A) ^b
-20	0.100 @ $V_{GS} = -4.5$ V	-2.4
	0.150 @ $V_{GS} = -2.5$ V	-2.0

FEATURES

- RoH Lead (Pb)-Free Version is RoHS Compliant



Available



Ordering Information: Si2301BDS-T1
Si2301BDS-T1—E3 (Lead (Pb)-Free)

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)					
Parameter		Symbol	5 sec	Steady State	Unit
Drain-Source Voltage		V_{DS}	-20		V
Gate-Source Voltage		V_{GS}	± 8		
Continuous Drain Current ($T_J = 150^\circ\text{C}$) ^b	$T_A = 25^\circ\text{C}$	I_D	-2.4	-2.2	A
	$T_A = 70^\circ\text{C}$		-1.9	-1.8	
Pulsed Drain Current ^a		I_{DM}	-10		
Continuous Source Current (Diode Conduction) ^b		I_S	-0.72	-0.6	W
Power Dissipation ^b	$T_A = 25^\circ\text{C}$	P_D	0.9	0.7	
	$T_A = 70^\circ\text{C}$		0.57	0.45	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	-55 to 150		$^\circ\text{C}$

THERMAL RESISTANCE RATINGS				
Parameter	Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient ^b	R_{thJA}	120	145	$^\circ\text{C/W}$
Maximum Junction-to-Ambient ^c		140	175	

Notes

- Pulse width limited by maximum junction temperature.
- Surface Mounted on FR4 Board, $t \leq 5$ sec.
- Surface Mounted on FR4 Board.

For SPICE model information via the Worldwide Web: <http://www.vishay.com/www/product/spice.htm>

SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Conditions	Limits			Unit
			Min	Typ	Max	
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = -250 μA	-20			V
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250 μA	-0.45		-0.95	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±8 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -20 V, V _{GS} = 0 V			-1	μA
		V _{DS} = -20 V, V _{GS} = 0 V, T _J = 55 °C			-10	
On-State Drain Current ^a	I _{D(on)}	V _{DS} ≤ -5 V, V _{GS} = -4.5 V	-6			A
		V _{DS} ≤ -5 V, V _{GS} = -2.5 V	-3			
Drain-Source On-Resistance ^a	r _{DS(on)}	V _{GS} = -4.5 V, I _D = -2.8 A		0.080	0.100	Ω
		V _{GS} = -2.5 V, I _D = -2.0 A		0.110	0.150	
Forward Transconductance ^a	g _{fs}	V _{DS} = -5 V, I _D = -2.8 A		6.5		S
Diode Forward Voltage	V _{SD}	I _S = -0.75 A, V _{GS} = 0 V		-0.80	-1.2	V
Dynamic^b						
Total Gate Charge	Q _g	V _{DS} = -6 V, V _{GS} = -4.5 V I _D ≅ -2.8 A		4.5	10	nC
Gate-Source Charge	Q _{gs}			0.7		
Gate-Drain Charge	Q _{gd}			1.1		
Input Capacitance	C _{iss}	V _{DS} = -6 V, V _{GS} = 0, f = 1 MHz		375		pF
Output Capacitance	C _{oss}			95		
Reverse Transfer Capacitance	C _{rss}			65		
Switching^c						
Turn-On Time	t _{d(on)}	V _{DD} = -6 V, R _L = 6 Ω I _D ≅ -1.0 A, V _{GEN} = -4.5 V R _g = 6 Ω		20	30	ns
	t _r			40	60	
Turn-Off Time	t _{d(off)}			30	45	
	t _f			20	30	







Notes

- a. Pulse test: PW ≤ 300 μs duty cycle ≤ 2%.
 b. For DESIGN AID ONLY, not subject to production testing.
 c. Switching time is essentially independent of operating temperature. • FaxBack 408-970-5600






Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.




TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)



TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)



TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?72066>.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.