

Full Size Clock Oscillators TTL/HCMOS Compatible



The XO-54 series oscillator is Full Size Tri-state Enable/Disable control. The metal package with pin #7 case ground acts as shielding to minimize EMI radiation.

FEATURES


- 14 pin full size
- Industry standard
- Wide frequency range
- Low cost
- Tri-State enable/disable
- Resistance weld package
- 5V

STANDARD ELECTRICAL SPECIFICATIONS

PARAMETER	SYMBOL	CONDITION	XO-54
Frequency Range	F_O		1MHz ~ 125.00MHz
Frequency Stability*		All Condition*	$\pm 25\text{ppm}$, $\pm 50\text{ppm}$, $\pm 100\text{ppm}$
Operating Temperature Range	T_{OPR}		$0^\circ\text{C} \sim 70^\circ\text{C}$ (- $40^\circ\text{C} \sim + 85^\circ\text{C}$ option)
Storage Temperature Range	T_{STG}		- $55^\circ\text{C} \sim + 125^\circ\text{C}$
Power Supply Voltage	V_{DD}		$5.0\text{V} \pm 10\%$
Aging (First Year)		$25^\circ\text{C} \pm 3^\circ\text{C}$	$\pm 5\text{ppm}$
Supply Current	I_{DD}	1MHz to 23.999MHz	20mA Max
		24.000MHz to 49.999MHz	30mA Max
		50.000MHz to 69.999MHz	40mA Max
		70.000MHz to 125.000MHz	60mA Max
Output Symmetry	Sym	$1/2V_{DD}$	40/60%(45/55% Option)
Rise Time	T_r	$10\%V_{DD} \sim 90\%V_{DD}$	10 nS Max
Fall Time	T_f	$90\%V_{DD} \sim 10\%V_{DD}$	10 nS Max
Output Voltage	V_{OH}		90% V_{DD} Min
	V_{OL}		10% V_{DD} Max
Output Load	TTL Load		1 ~ 10TTL
	HCMOS Load		~ 50M : 50pF
			~ 70M : 30pF
Start-up Time		T_s	~100M : 15pF 10mS Max
Pin 1, Tri-State Function			Pin 1 = H or open.... Output active at pin 8 Pin 1 = L.... High Impedance at pin 8

*Include: 25°C tolerance, operating temperature range, input voltage change, aging, load change, shock and vibration.

DIMENSIONS in millimeters



ORDERING INFORMATION

XO-54 MODEL	B FREQUENCY STABILITY	R OTR	E ENABLE/DISABLE	40M FREQUENCY/MHz
	AA = 0.0025% (25PPM) A = 0.005% (50PPM) B = 0.01% (100PPM) Standard	Blank = 0°C to $+ 70^\circ\text{C}$ R = - 40°C to $+ 85^\circ\text{C}$	Blank = Pin 1 open E = Disable or Tristate	