



High Current Density Surface Mount Ultrafast Rectifiers

eSMP™ Series



DO-220AA (SMP)

FEATURES

- Very low profile - typical height of 1.0 mm
- Ideal for automated placement
- Glass passivated chip junction
- Ultrafast recovery times for high frequency
- Low forward voltage drop, low power loss
- Low thermal resistance
- Meets MSL level 1 per J-STD-020C, LF max peak of 260 °C
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



MAJOR RATINGS AND CHARACTERISTICS

$I_{F(AV)}$	2 A
V_{RRM}	100 V, 150 V, 200 V
t_{rr}	25 ns
V_F at $I_F = 2$ A	0.75 V
T_j max.	175 °C

TYPICAL APPLICATIONS

For use in secondary rectification and free-wheeling for ultrafast switching speeds of ac-to-ac and dc-to-dc converters in high temperature conditions for both consumer and automotive applications.

MECHANICAL DATA

Case: DO-220AA (SMP)

Epoxy meets UL 94V-0 flammability rating

Terminals: Matte tin plated leads, solderable per J-STD-002B and JESD22-B102D

E3 suffix for commercial grade, HE3 suffix for high reliability grade (AEC Q101 qualified)

Polarity: Color band denotes cathode end

MAXIMUM RATINGS ($T_A = 25$ °C unless otherwise noted)

PARAMETER	SYMBOL	ESH2PB	ESH2PC	ESH2PD	UNIT
Device marking code		P2B	P2C	P2D	
Maximum repetitive peak reverse voltage	V_{RRM}	100	150	200	V
Maximum average forward rectified current (Fig. 1)	$I_{F(AV)}$	2.0			A
Peak forward surge current 10 ms single half sine-wave superimposed on rated load	I_{FSM}	50			A
Operating junction and storage temperature range	T_J, T_{STG}	- 55 to + 175			°C

ELECTRICAL CHARACTERISTICS ($T_A = 25$ °C unless otherwise noted)

PARAMETER	TEST CONDITIONS	SYMBOL	TYP.	MAX.	UNIT
Maximum instantaneous forward voltage ⁽¹⁾	at $I_F = 2$ A, $T_j = 25$ °C at $I_F = 2$ A, $T_j = 125$ °C	V_F	0.90 0.75	0.98 0.82	V
Maximum reverse current ⁽¹⁾	at rated V_R $T_j = 25$ °C $T_j = 125$ °C	I_R	0.2 12.6	1.0 25	μA
Maximum reverse recovery time	at $I_F = 0.5$ A, $I_R = 1$ A, $I_{rr} = 0.25$ A	t_{rr}	-	25	ns



ELECTRICAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)					
PARAMETER	TEST CONDITIONS	SYMBOL	TYP.	MAX.	UNIT
Typical reverse recovery time	at $I_F = 1.0\text{ A}$, $V_R = 30\text{ V}$ di/dt = 50 A/ μs , $I_{rr} = 10\% I_{RM}$ $T_j = 25\text{ }^\circ\text{C}$ at $I_F = 1.0\text{ A}$, $V_R = 30\text{ V}$ di/dt = 50 A/ μs , $I_{rr} = 10\% I_{RM}$ $T_j = 100\text{ }^\circ\text{C}$	t_{rr}	- -	25 35	ns
Typical stored charge	at $I_F = 1.0\text{ A}$, $V_R = 30\text{ V}$ di/dt = 50 A/ μs , $I_{rr} = 10\% I_{RM}$ $T_j = 25\text{ }^\circ\text{C}$ at $I_F = 1.0\text{ A}$, $V_R = 30\text{ V}$ di/dt = 50 A/ μs , $I_{rr} = 10\% I_{RM}$ $T_j = 100\text{ }^\circ\text{C}$	Q_{rr}	- -	10 15	nC
Typical junction capacitance	at 4.0 V, 1 MHz	C_J	-	25	pF

Note:

(1) Pulse test: 300 μs pulse width, 1 % duty cycle

THERMAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)					
PARAMETER	SYMBOL	ESH2PB	ESH2PC	ESH2PD	UNIT
Typical thermal resistance ⁽¹⁾	$R_{\theta JA}$ $R_{\theta JL}$ $R_{\theta JC}$		80 15 22		$^\circ\text{C/W}$

Note:

(1) Thermal resistance from junction to ambient and junction to lead mounted on P.C.B. with 6.0 x 6.0 mm copper pad areas. $R_{\theta JL}$ is measured at the terminal of cathode band. $R_{\theta JC}$ is measured at the top centre of the body

ORDERING INFORMATION (Example)				
PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
ESH2PB-E3/84A	0.024	84A	3000	7" Diameter Plastic Tape & Reel
ESH2PB-E3/85A	0.024	85A	10000	13" Diameter Plastic Tape & Reel
ESH2PBHE3/84A ⁽¹⁾	0.024	84A	3000	7" Diameter Plastic Tape & Reel
ESH2PBHE3/85A ⁽¹⁾	0.024	85A	10000	13" Diameter Plastic Tape & Reel

Note:

(1) Automotive grade AEC Q101 qualified

RATINGS AND CHARACTERISTICS CURVES

($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Figure 1. Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Instantaneous Forward Characteristics




Figure 5. Typical Junction Capacitance





Figure 4. Typical Reverse Leakage Characteristics

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

DO-220AA (SMP)





Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.