

## Aluminum Capacitors SMD (Chip) Long Life




Fig.1 Component outlines



### FEATURES

- Polarized aluminum electrolytic capacitors, non-solid electrolyte, self healing.
- Extended voltage and capacitance range.
- SMD-version, fully moulded, insulated.
- Flexible terminals, reflow and wave solderable.
- Compact, rectangular shape.
- Charge and discharge proof, no peak current limitation.
- Supplied in blister tape on reel.

QUICK REFERENCE DATA	
DESCRIPTION	VALUE
Nominal case sizes (L x W x H in mm)	14.3 x 6.2 x 6.9 and 14.3 x 7.6 x 8.2
Rated capacitance range, C <sub>R</sub>	1.0 to 220 µF
Tolerance on C <sub>R</sub>	±20%
Rated voltage range, U <sub>R</sub>	6.3 to 100 V
Category temperature range	-55 to +105°C
Endurance test at 105 °C	1000 hours
Useful life at 105 °C	2000 hours
Useful life at 40 °C ; 1.3 x I <sub>R</sub> applied	200000 hours
Shelf life at 0 V, 105 °C	500 hours
Resistance to soldering heat test	immersion in solder: 10 s at 260 °C or 40 s at 215 °C
Based on sectional specification	IEC 60384-18/CECC 32300
Climatic category IEC 60068	55/105/56

### APPLICATIONS

- SMD technology.
- Industrial and professional applications.
- Telecommunications, automotive, EDP general industrial.
- Coupling, decoupling, smoothing, filtering, buffering, timing.

### MARKING

- Rated capacitance (in µF).
- Rated voltage (in V).
- Date code in accordance with IEC 60062.
- Name of manufacturer.
- '-' sign indicating the cathode. The anode is identified by bevelled edges.
- Series number (139).

SELECTION CHART FOR C <sub>R</sub> , U <sub>R</sub> AND RELEVANT NOMINAL CASE SIZES (L x W x H in mm)								
C <sub>R</sub> (µF)	U <sub>R</sub> (V)							
	6.3	10	16	25	40	50	63	100
1.0	-	-	-	-	-	-	-	14.3 x 6.2 x 6.9
2.2	-	-	-	-	-	-	-	14.3 x 6.2 x 6.9
3.3	-	-	-	-	-	-	-	14.3 x 6.2 x 6.9
4.7	-	-	-	-	-	-	-	14.3 x 6.2 x 6.9
10	-	-	-	14.3 x 6.2 x 6.9	-	14.3 x 6.2 x 6.9	14.3 x 7.6 x 8.2	-
15	-	-	-	-	14.3 x 6.2 x 6.9	14.3 x 7.6 x 8.2	-	-
22	-	-	-	14.3 x 6.2 x 6.9	-	14.3 x 7.6 x 8.2	-	-

<b>SELECTION CHART FOR <math>C_R</math>, <math>U_R</math> AND RELEVANT NOMINAL CASE SIZES (L x W x H in mm)</b>								
$C_R$ ( $\mu\text{F}$ )	$U_R$ (V)							
	6.3	10	16	25	40	50	63	100
33	-	-	-	14.3 x 6.2 x 6.9	14.3 x 7.6 x 8.2	-	-	-
47	-	-	14.3 x 6.2 x 6.9	14.3 x 7.6 x 8.2	-	-	-	-
68	-	14.3 x 6.2 x 6.9	-	-	-	-	-	-
100	14.3 x 6.2 x 6.9	-	14.3 x 7.6 x 8.2	-	-	-	-	-
150	-	14.3 x 7.6 x 8.2	-	-	-	-	-	-
220	14.3 x 7.6 x 8.2	-	-	-	-	-	-	-


**DIMENSIONS** in millimeters


Fig.2 Dimensional outline.

Table 1

DIMENSIONS in millimeters, MASS AND PACKAGING QUANTITIES										
NOMINAL CASE SIZE $L \times W \times H$	CASE CODE	$L_{\max}$	$W_{\max}$	$H_{\max}$	$O_{\max}$	$S$	$G_{\max}$	$R_{\min}$	MASS (g)	PACKAGING QUANTITIES PER REEL
14.3 x 6.2 x 6.9	2	14.5	6.3	7.05	13.0	2.15	7.5	4.7	~0.95	700
14.3 x 7.6 x 8.2	3	14.5	7.7	8.35	13.0	2.85	7.5	4.7	~1.3	700

**Note**

1. Detailed tape dimensions see section 'PACKAGING'.

Table 2

<b>RECOMMENDED SOLDERING PAD DIMENSIONS</b> in millimeters (placement accuracy $\pm 0.25\text{mm}$ )														
<b>NOMINAL CASE SIZE</b> <b>L × W × H</b>	<b>FOR REFLOW SOLDERING</b>							<b>FOR WAVE SOLDERING</b>						
	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>	<b>G</b>	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>	<b>G</b>
14.3 × 6.2 × 6.9	15.8	8.8	3.5	2.8	8.0	16.2	7.7	18.6	10.0	4.3	5.0	8.8	20.5	11.5
14.3 × 7.6 × 8.2	15.8	8.8	3.5	2.8	8.0	16.2	9.1	18.6	10.0	4.3	6.0	8.8	21.5	13.0

## MOUNTING

The capacitors are designed for automatic placement on to printed-circuit boards or hybrid circuits.

Optimum dimensions of soldering pads depend amongst others on soldering method, mounting accuracy, print lay-out and/or adjacent components.

For recommended soldering pad dimensions, refer to Fig.3 and Table 2.




Fig.3 Recommended pad dimensions for reflow and wave soldering.

## SOLDERING

Soldering conditions are defined by the curve, temperature versus time, where the temperature is that measured on the soldering pad during processing.

For maximum conditions of different soldering methods see Figs 4, 5 and 6.

Any temperature versus time curve which does not exceed the specified maximum curves may be applied.

AS A GENERAL PRINCIPLE, TEMPERATURE AND DURATION SHALL BE THE **MINIMUM** NECESSARY REQUIRED TO ENSURE GOOD SOLDERING CONNECTIONS. HOWEVER, THE SPECIFIED MAXIMUM CURVES SHOULD NEVER BE EXCEEDED.

Table 3

<b>CURING CONDITIONS FOR SMD-GLUE</b>	
<b>MAX. <math>T_{amb}</math> (°C)</b>	<b>MAX. EXPOSURE TIME (minutes)</b>
125	30
140	10
150	5
160	2




Fig.4 Maximum temperature load during infrared reflow soldering.




Fig.5 Maximum temperature load during vapour phase reflow soldering.




Fig.6 Maximum temperature load during (double-) wave soldering.

### ELECTRICAL DATA

SYMBOL	DESCRIPTION
$C_R$	rated capacitance at 100 Hz , tolerance $\pm 20\%$
$I_R$	rated RMS ripple current at 100 Hz , $105^\circ C$
$I_{L5}$	max. leakage current after 5 minutes at $U_R$
$\tan \delta$	max. dissipation factor at 100 Hz
$Z$	max. impedance at 10 kHz

### ORDERING EXAMPLE

Electrolytic capacitor 139 series

$100 \mu F/16 V; \pm 20\%$

Nominal case size:  $14.3 \times 7.6 \times 8.2$  mm; taped on reel

Catalog number: 2222 139 65101.

### Note

- Unless otherwise specified, all electrical values in Table 4 apply at  $T_{amb} = 20^\circ C$ ,  $P = 86$  to  $106$  kPa,  $RH = 45$  to  $75\%$ .

Table 4


ELECTRICAL DATA AND ORDERING INFORMATION							
$U_R$ (V)	$C_R$ 100 Hz ( $\mu F$ )	NOMINAL CASE SIZE $L \times W \times H$ (mm)	$I_R$ 100 Hz $105^\circ C$ (mA)	$I_{L5}$ 5 min ( $\mu A$ )	$\tan \delta$ 100 Hz	$Z$ 10 kHz ( $\Omega$ )	CATALOG NUMBER 2222 139 .....
6.3	100	$14.3 \times 6.2 \times 6.9$	79	4.3	0.24	3.0	63101
	220	$14.3 \times 7.6 \times 8.2$	120	5.8	0.24	1.4	63221
10	68	$14.3 \times 6.2 \times 6.9$	71	4.4	0.20	2.9	64689
	150	$14.3 \times 7.6 \times 8.2$	110	6.0	0.20	1.3	64151
16	47	$14.3 \times 6.2 \times 6.9$	66	4.5	0.16	3.4	65479
	100	$14.3 \times 7.6 \times 8.2$	100	6.2	0.16	1.6	65101
25	10	$14.3 \times 6.2 \times 6.9$	40	3.5	0.09	12	66109
	22	$14.3 \times 6.2 \times 6.9$	48	4.1	0.14	5.5	66229
	33	$14.3 \times 6.2 \times 6.9$	59	4.7	0.14	3.7	66339
	47	$14.3 \times 7.6 \times 8.2$	79	5.4	0.14	2.6	66479
40	15	$14.3 \times 6.2 \times 6.9$	45	4.2	0.11	6	67159
	33	$14.3 \times 7.6 \times 8.2$	75	5.6	0.11	2.7	67339
50	10	$14.3 \times 6.2 \times 6.9$	40	4.0	0.09	7	61109
	15	$14.3 \times 7.6 \times 8.2$	56	4.5	0.09	4.7	61159
	22	$14.3 \times 7.6 \times 8.2$	67	5.2	0.09	3.2	61229

**ELECTRICAL DATA AND ORDERING INFORMATION**

$U_R$ (V)	$C_R$ 100 Hz ( $\mu$ F)	NOMINAL CASE SIZE $L \times W \times H$ (mm)	$I_R$ 100 Hz 105 °C (mA)	$I_{L5}$ 5 min ( $\mu$ A)	Tan $\delta$ 100 Hz	$Z$ 10 kHz ( $\Omega$ )	CATALOG NUMBER
63	2.2	14.3 × 6.2 × 6.9	19	3.3	0.09	25	68228
	3.3	14.3 × 6.2 × 6.9	23	3.4	0.09	21	68338
	4.7	14.3 × 6.2 × 6.9	28	3.6	0.09	17	68478
	10	14.3 × 7.6 × 8.2	48	4.3	0.08	8	68109
100	1.0	14.3 × 6.2 × 6.9	12	3.2	0.09	55	69108
	2.2	14.3 × 6.2 × 6.9	19	3.4	0.09	29	69228
	3.3	14.3 × 7.6 × 8.2	27	3.7	0.08	17	69338
	4.7	14.3 × 7.6 × 8.2	33	3.9	0.08	11	69478


**ADDITIONAL ELECTRICAL DATA**

PARAMETER	CONDITIONS	VALUE
<b>Voltage</b>		
Surge voltage for short periods		$U_S \leq 1.15 \times U_R$
Reverse voltage		$U_{rev} \leq 1 \text{ V}$
<b>Current</b>		
Leakage current	after 1 minute at $U_R$	$I_{L1} \leq 0.02 C_R \times U_R + 3$
	after 5 minute at $U_R$	$I_{L5} \leq 0.002 C_R \times U_R + 3 \mu\text{A}$
<b>Inductance</b>		
Equivalent series inductance (ESL)	nominal case size 14.3 × 6.2 × 6.9 mm	typ. 18 nH
	nominal case size 14.3 × 7.6 × 8.2 mm	typ. 28 nH
<b>Resistance</b>		
Equivalent series resistance (ESR)	calculated from $\tan \delta_{max}$ and $C_R$ (see Table 4)	$ESR = \tan \delta / 2\pi f C_R$

**CAPACITANCE (C)**

$C_0$  = capacitance at 20°C, 100Hz.

Fig.7 Typical multiplier of capacitance as a function of ambient temperature.



$C_0$  = capacitance at 20°C, 100Hz.

$T_{amb} = 20 \text{ }^{\circ}\text{C}$

Fig.8 Typical multiplier of capacitance as a function of frequency.


**RIPPLE CURRENT AND USEFUL LIFE**


Fig.9 Multiplier of useful life as a function of ambient temperature and ripple current load.

**Table 5**

<b>MULTIPLIER OF RIPPLE CURRENT (<math>I_R</math>) AS A FUNCTION OF FREQUENCY</b>			
FREQUENCY (Hz)	<b><math>I_R</math> MULTIPLIER</b>		
	$U_R = 6.3 \text{ to } 16 \text{ V}$	$U_R = 25 \text{ to } 50 \text{ V}$	$U_R = 63 \text{ to } 100 \text{ V}$
50	0.95	0.90	0.85
100	1.00	1.00	1.00
300	1.07	1.12	1.20
1000	1.12	1.20	1.30
3000	1.15	1.25	1.35
$\geq 10000$	1.20	1.30	1.40

Table 6

<b>TEST PROCEDURES AND REQUIREMENTS</b>			
<b>TEST</b>		<b>PROCEDURE (quick reference)</b>	<b>REQUIREMENTS</b>
<b>NAME OF TEST</b>	<b>REFERENCE</b>		
Mounting	IEC 60384-18, subclause 4.3	shall be performed prior to tests mentioned below; reflow or (double-) wave soldering; for maximum temperature load refer to chapter "Mounting"	$\Delta C/C: \pm 5\%$ $\tan \delta \leq \text{spec. limit}$ $I_{L5} \leq \text{spec. limit}$
Endurance	IEC 60384-18/ CECC 32300, subclause 4.15	$T_{amb} = 105^{\circ}\text{C}$ ; $U_R$ applied; 1000 hours	$U_R \leq 6.3 \text{ V } \Delta C/C: +15/-30\%$ $U_R \geq 10 \text{ V } \Delta C/C: \pm 15\%$ $\tan \delta \leq 1.3 \times \text{spec. limit}$ $Z \leq 2 \times \text{spec. limit}$ $I_{L5} \leq \text{spec. limit}$
Useful life	CECC 30301, subclause 1.8.1	$T_{amb} = 105^{\circ}\text{C}$ ; $U_R$ and $I_R$ applied; 2000 hours	$U_R \leq 6.3 \text{ V } \Delta C/C: +45/-50\%$ $U_R \geq 10 \text{ V } \Delta C/C: \pm 45\%$ $\tan \delta \leq 3 \times \text{spec. limit}$ $Z \leq 3 \times \text{spec. limit}$ $I_{L5} \leq \text{spec. limit}$ no short or open circuit total failure percentage: $\leq 1\%$
Shelf life (storage at high temperature)	IEC 60384-18/ CECC 32300, subclause 4.17	$T_{amb} = 105^{\circ}\text{C}$ ; no voltage applied; 500 hours after test: $U_R$ to be applied for 30 minutes, 24 to 48 hours before measurement	for requirements see 'Endurance test' above



## Legal Disclaimer Notice

Vishay

### Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.