




Ceramic AC Capacitors

Class X1, 440 V_{AC}/Class Y2, 250 V_{AC}



• Dimensions in mm

Impedance (Z) as a function of frequency (f) at T_a = 20 °C (average). Measurement with lead length 6 mm.



DESIGN:

Disc capacitors with epoxy coating

RATED VOLTAGE U_R:

(X1): 440 V_{AC}, 50 Hz (IEC 60384-14.2)
 (Y2): 250 V_{AC}, 50 Hz (IEC 60384-14.2)
 250 V_{AC}, 60 Hz (UL1414, CSA C22.2)

DIELECTRIC STRENGTH BETWEEN LEADS:

Component test:

2500 V_{AC}, 50 Hz, 2 s, for parts with pitch ≥ 7.5 mm

As repeated test admissible only once with

2000 V_{AC}, 50 Hz, 2 s

Random sampling test (destructive test):

1500 V_{AC}, 50 Hz, 60 s

DIELECTRIC STRENGTH OF BODY INSULATION:

2000 V_{AC}, 50 Hz, 60 s (destructive test)

DISSIPATION FACTOR tan δ:

≤ 25 • 10⁻³

INSULATION RESISTANCE R_{is}:

≥ 6 • 10⁹ Ω

CATEGORY TEMPERATURE RANGE θ_A:

(- 40 to + 125) °C

CLIMATIC CATEGORY ACC. TO EN60068-1:

40/125/21

COATING:

Epoxy, dipped, insulating, flame retarding acc. to UL 94V-0

TAPING AND SPECIAL LEAD CONFIGURATIONS:

On request

MARKING (EXAMPLE):



WYO 1 nF to 2.5 nF



WYO 3.3 nF to 12 nF

All approval marks are also shown on the label.

**WYO**

Ceramic AC Capacitors
Class X1, 440 V_{AC}/Class Y2, 250 V_{AC}

Vishay Draloric**ORDERING INFORMATION, CERAMIC X1 / Y2 CAPACITORS WYO**

CAPACITANCE (pF)	TOL. (%)	D x s (mm)	F ± 1* (mm)	d ± 0.05* (mm)	V ± 0.5* (mm)	ORDERING CODE
1000	± 20 %	6.5 x 4.5	5.0	0.6	1.4	WYO102□CM□□□KR
1500		8.0 x 4.5				WYO152□CM□□□KR
1800		8.0 x 4.5				WYO182□CM□□□KR
2200		9.0 x 4.5				WYO222□CM□□□KR
2500		9.0 x 4.5				WYO252□CM□□□KR
3300		10.0 x 4.5	WYO332□CM□□□KR			
4700		12.0 x 4.5	WYO472□CM□□□KR			
5000		12.0 x 4.5	WYO502□CM□□□KR			
6800		17.0 x 4.5	1.6		WYO682□CM□□□KR	
8200		17.0 x 4.5			WYO822□CM□□□KR	
0.010 μF		21.0 x 4.5			WYO103□CM□□□KR	
0.012 μF		21.0 x 4.5			WYO123□CM□□□KR	
			7.5			

* Standard lead configuration, other lead spacing and diameter available on request.

ORDERING CODE

□	7th digit	Capacitance Tolerance	± 20 % = M
□□□	10th to 12th digit	Lead Configuration (see General Information)	
R	14th digit	RoHS Compliant Component	

APPROVALS**IEC 60384 - 14 / 2nd Issue (1993) incl. Am. 1 (1995) - Safety Tests****EN 132 400 (1994) - Safety Tests**

That approval together with the CB Test Certificate substitutes the national approval of the following nations:

Belgium	France	Italy	Austria	China	Japan	Spain
Denmark	Greece	Luxembourg	Portugal	Singapore	Poland	United Kingdom
Germany	Ireland	Netherlands	Sweden	Slovenia	Hungaria	Czech Republic
Finland	Iceland	Norway	Switzerland	Korea	Israel	

Y2 - Capacitor: CB-Test Certificate: DE-1-11476-A1 1 nF ... 12 nF 250 Vac
X1 - Capacitor: CB-Test Certificate: DE-1-11148-A1 1 nF ... 12 nF 440 Vac
Minimum thickness of insulation: 0.4 mm



Underwriters Laboratories Inc.

UL 1414	Line-by-pass component	1 nF ... 12 nF	250 Vac	
	Agency Files / Licences	E 183 844 V1 S2		

Canadian Standards Association

CSA C22.2 No 1-98	Line-by-pass component	1 nF ... 12 nF	250 Vac	
	Agency Files / Licences	E 183 844 V1 S2		

ORDERING INFORMATION

WYO	103	M	CM	CF0	K	R
SERIES	CAP. VALUE	TOLERANCE	RATED VOLTAGE	LEAD CONFIGURATION	INTERNAL CODE	RoHS COMPLIANT



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.