




100 series


D-SUB SOLDER TYPE

| Position | A | B | C | D | E |
|----------|-------|-------|-------|-------|-------|
| 9 | 16.92 | 24.99 | 30.81 | 19.36 | 16.33 |
| 15 | 25.25 | 33.32 | 39.14 | 27.64 | 24.66 |
| 25 | 38.96 | 47.04 | 53.04 | 41.08 | 38.38 |
| 37 | 55.42 | 63.50 | 69.32 | 57.38 | 54.84 |

[MALE]



[FEMALE]



Specifications:

Contact Resistance: 30m Ω max.at DC 100 mA
 Insulator Resistance: 1000M Ω min.at DC 500V
 Current Rating: 5AMP

Dielectric Withstanding

Voltage: AC 1000V For 1 minute
 Operating Temperature: -55° C--+105° C
 Contact: Brass or Phosphor Bronze
 Housing: PBT &30% Glass Fiber(UL 94V-0)

How To Order

100 -09 P C B N S

1 2 3 4 5 6 7

SERIES NO

NO.OF PINS:
09.15.25.37.

CONTACT TYPE
P-MALE
S-FEMALE

SHELL PLATED:
C-CHROMATED SHELL
T-TIN SHELL

PIN TYPE:
S-STAMPED PIN

OPTION ON SCREW:
N-W/O SCREWS
Y-WITH SCREW(4-40UNC)

OPION ON INSULATOR:
B-BLUE
K-BLACK
W-WHITE