

# 101 series

## D-SUB DIP STRAIGHT TYPE

Position	A	B	C	D	E
9	17.78	24.99	31.04	19.36	16.33
15	26.15	33.32	39.24	27.64	24.66
25	39.94	47.04	53.04	41.08	38.38
37	56.56	63.50	69.62	57.38	54.84

### Specifications:

Contact Resistance: 30m  $\Omega$  max.at DC 100 mA  
 Insulator Resistance: 1000M  $\Omega$  min.at DC 500V  
 Current Rating: 5AMP

### Dielectric Withstanding


Voltage: AC 1000V For 1 minute  
 Operating Temperature: -55° C-->+105° C  
 Contact: Brass or Phosphor Bronze  
 Housing: PBT &30% Glass Fiber(UL 94V-0)

### How To Order

101 -09 P C B N S

SERIES NO: 1  
 NO. OF PINS: 2 3 4 5 6 7  
 CONTACT TYPE: P-MALE, S-FEMALE  
 SHELL PLATED: C-CHROMATED SHELL, T-TIN SHELL  
 PIN TYPE: S-STAMPED PIN  
 OPTION ON SCREW: N-W/O SCREWS, Y-WITH SCREW(4-40UNC)  
 OPTION ON INSULATOR: B-BLUE, K-BLACK, W-WHITE

### [ MALE ]



### [ FEMALE ]

