

# 103 series

## D-SUB I.D.C. TYPE

Position	A	B	C	D	E
9	17.78	24.99	31.04	19.36	16.33
15	26.15	33.32	39.24	27.64	24.66
25	39.94	47.04	53.04	41.08	38.38
37	56.56	63.50	69.62	57.38	54.84

### Specifications:

Contact Resistance: 30mΩ max.at DC 100 mA  
 Insulator Resistance: 1000MΩ min.at DC 500V  
 Current Rating: 1AMP

### Dielectric Withstanding

Voltage: AC 500V For 1 minute  
 Operating Temperature: -55° C--+105° C  
 Contact: Male Brass  
 Female Phosphor Bronze  
 Housing: PBT &30% Glass Fiber(UL 94V-0)

### How To Order

103 - 09 P M B 1


SERIES NO — 1  
 NO.OF PINS: — 2 3 4 5 6  
 CONTACT TYPE — P-MALE  
 S-FEMALE

OPTION OF FLANGE:  
 1-FLANGE WITH 4-40 UNC  
 2-FLANGE W/O 4-40UNC

OPION ON INSULATOR:  
 B-BLUE

OPION ON SHELL:  
 M-METAL SHELL

### [ MALE ]



### [ FEMALE ]

