


# 126 series

IC SOCKET 2.54mm(0.100")

Position	Dimension				Position	Dimension			
	A	B	C	D		A	B	C	D
6	7.52	7.62	10.16	7.62	24	30.48	27.94	10.16	7.62
8	10.16	7.62	10.16	7.62	24	30.48	27.94	17.78	15.24
14	17.82	15.24	10.16	7.62	28	35.56	33.02	10.16	7.62
16	20.32	17.78	10.16	7.62	28	35.56	33.02	17.78	15.24
18	22.86	20.32	10.16	7.62	40	50.80	48.26	17.78	15.24
20	25.40	22.86	10.16	7.62					



## Specifications:

Contact Resistance: 30mΩ max.at DC 100 mA  
 Insulator Resistance: 1000MΩ min.at DC 500V  
 Current Rating: 1AMP

## Dielectric Withstanding

Voltage: AC 500V For 1 minute  
 Operating Temperature: -55° C--+105° C  
 Contact: Phosphor Bronze  
 Housing: PBT &30% Glass Fiber(UL 94V-0)

## How To Order

126 -3 08 R T M

SERIES NO 1 2 3 4 5 6  
 DIMENSION' D' 3-7.62mm 6-15.24mm  
 NO.OF PINS: 6.8.14.16.18.20. 24.28.40.  
 M-SMT TYPE ONLY  
 CONTACT PLATED:  
 T-OUTSIDE TIN PLATED&  
 INSIDE GOLD PLATED  
 G-ALL GOLD PLATED  
 R-ROUND PIN

