


# 132 series


## PH CONNECTOR 2.00mm(0.079")

Position	A	B	C	D	Position	A	B	C	D
2	2.0	5.9	2.0	5.8	10	18.0	21.9	18.0	21.8
3	4.0	7.9	4.0	7.8	11	20.0	23.9	20.0	23.8
4	6.0	9.9	6.0	9.8	12	22.0	25.9	22.0	25.8
5	8.0	11.9	8.0	11.8	13	24.0	27.9	24.0	27.8
6	10.0	13.9	10.0	13.8	14	26.0	29.9	26.0	29.8
7	12.0	15.9	12.0	15.8	15	28.0	31.9	28.0	31.8
8	14.0	17.9	14.0	17.8	16	30.0	33.9	30.0	33.8
9	16.0	19.9	16.0	19.8					


### [STRAIGHT]



### [RIGHT ANGLE]




### [HOUSING]



### [TERMINALS]

A-AU

B-BU



### Material & Finish

Insulator Material: Nylon 66(UL 94V-0)

Contact Material: Brass or Phosphor Bronze

Contact Plated: Tin plated

Number of Contacts: 2 Thru 16

### How To Order

132 -09 S T

1 2 3 4

SERIES NO

NO. OF PINS:  
2 TO 16

S-STRAIGHT TYPE

R-RIGHT ANGLE TYPE

H-HOUSING(WITH TERMINALS)

CONTACT PLATED:

T-TIN PLATED

G-GOLD PLATED